

MAX 25~50KTL3-XL

- 6MPPTs
- Smart diagnosis
- High efficiency up to 99%
- Local WIFI connection
- String monitoring
- AC&DC type II SPD
- AFCI protection



P O W E R
- I N G O
T O M O -
R R O W O

Growatt
powering tomorrow

www.ginverter.com

Datasheet	MAX 25KTL3-XL	MAX 30KTL3-XL	MAX 35KTL3-XL	MAX 40KTL3-XL	MAX 50KTL3-XL
Input data (DC)					
Max, recommended PV power (for module STC)	37500W	45000W	52500W	60000W	75000W
Max,DC voltage	1100V				
Start voltage	250V				
Nominal voltage	360V				450V
MPPT voltage range	200V-1000V				
No. of MPP trackers	6				
No. of PV strings per MPP tracker	2				
Max. input current per MPP tracker	26A				
Max. short-circuit current per MPP tracker	32A				
Output data (AC)					
AC nominal power	25000W	30000W	35000W	40000W	50000W
Max. AC apparent power	27700VA	33300VA	38800VA	44400VA	50000VA
Nominal AC voltage (range*)	133V/230V				
AC grid frequency (range*)	50/60 Hz (47,5-52Hz/55-65 Hz)				
Max. output current	69,5A	83,6A	97,4A	111,5A	125,5A
Adjustable power factor	0,8leading ...0,8lagging				
THDi	<3%				
AC grid connection type	3W+PE				
Efficiency					
Max,efficiency	98,70%		98,80%		
European efficiency	98,2%		98,30%		
Protection devices					
DC reverse polarity protection	Yes				
DC switch	Yes				
AC/DC surge protection	Type II				
Insulation resistance monitoring	Yes				
AC short-circuit protection	Yes				
Ground fault monitoring	Yes				
Grid monitoring	Yes				
Anti-islanding protection	Yes				
Residual-current monitoring unit	Yes				
String monitoring	Yes				
AFCI protection	Yes				
General data					
Dimensions (W / H / D)	860/600/300mm				
Weight	82kg				
Operating temperature range	-25°C ... +60°C(>45°C Derating)				
Noise emission (typical)	≤60dB(A)				
Self-consumption	1W				
Topology	Transformerless				
Cooling	Fan cooling				
Protection degree	IP65				
Relative humidity	0-100%				
Altitude	4000m				
DC connection	H4				
AC connection	Cable gland+OT terminal				
Display	LED/WIFI+APP				
Interfaces: RS485 / USB /WIFI/GPRS/4G	Yes/Yes /Optional/Optional/Optional				
CE ,EN50549					