



OPTIC G2 L QUICK ISO

Downlight made for a sustainable future – easily dismantled via a module system to save time when recycling. Big brother of the Optic family, perfect for high ceilings. Low build, suited for installation in 28mm secondary spaced boarding and directly against insulation. Modern LED and reflector technology with good glare-free light distribution and high lumen output. Tiltable 30°, which also makes it the perfect choice for sloping ceilings. Very good colour rendering, Ra>95. Driver with cover that can be adapted for cable or flex hose 16mm. Comes with 3-pole push-in terminal for through wiring and strain relief. This luminaire is dimmable with the most commonly available dimmers on the market.

SAME QUICK
INSTALLATION

- Lifetime L80 100 000h Ta25°
- Newly developed dimmable driver with combined cover for cable or flex hose 16mm
- Replaceable LED and driver – built for the future
- Tilts 30° – perfect for angled and high ceilings
- Low-build, perfect for secondary spaced boarding 28mm with 13mm plaster
- Approved for installation directly against insulation
- Can be installed both indoors and outdoors



The Optic-family is growing!

Works just as well
against insulation as
against firm ceiling





For secondary spaced boarding 28mm with 13mm plaster

OPTIC G2 L QUICK ISO





E-nr	Colour	Colour temperature	Luminaire lumen	Beam angle	Effect luminaire
7392971146904 ¹⁾	White	Tune 2000-2700K	460lm	36°	7,5W
7392971146911	White	2700K	610lm	36°	7,5W
7392971146928	White	3000K	640lm	36°	7,5W
7392971146935	White	4000K	670lm	36°	7,5W
7392971146942 ¹⁾	Black	Tune 2000-2700K	460lm	36°	7,5W
7392971146959	Black	2700K	610lm	36°	7,5W
7392971146966	Black	3000K	640lm	36°	7,5W
7392971146973	Black	4000K	670lm	36°	7,5W



OPTIC G2 L QUICK ISO DALI



E-nr	Colour	Colour temperature	Luminaire lumen	Beam angle	Effect luminaire
7392971147017 ¹⁾	Vit	Tune 2000-2700K	460lm	36°	7,5W
7392971147024	Vit	2700K	610lm	36°	7,5W
7392971147031	Vit	3000K	640lm	36°	7,5W



OPTIC G2 L QUICK ISO 6-PACK

Convenient 6-pack for easier transport and fewer packages.
Includes six fixtures with phase dimmable driver in bag with handle.



E-nr	Colour	Colour temperature	Luminaire lumen	Beam angle	Effect luminaire
7392971146980 ¹⁾	Vit	Tune 2000-2700K	460lm	36°	7,5W
7392971146997	Vit	2700K	610lm	36°	7,5W
7392971147000	Vit	3000K	640lm	36°	7,5W

