

**Switch-disconnector, DMM, 125 A, 3P + N (solid), Stop Function optional,
Without rotary handle and drive shaft, Vertical connection**



Part no. **DMM-125/1-SK**
1314203

Product name	Eaton DMM Switch-disconnector
Part no.	DMM-125/1-SK
EAN	8711426691346
Product Length/Depth	152 millimetre
Product height	108 millimetre
Product width	132 millimetre
Product weight	0.9 kilogram
Certifications	EAC KEMA IEC/EN 60204 VDE 0660 CE RoHS Lloyds IEC/EN 60947 IEC/EN 60947-3
Product Tradename	DMM
Product Type	Switch-disconnector
Product Sub Type	None
Globally Marketable	Yes
	Rated Short-time Withstand Current (Icw) for a time of 1 second Without rotary handle and drive shaft
Features	Version as main switch Version as maintenance-/service switch
Functions	Optional Stop Function
Number of poles	Three-pole + N
Accessories	Auxiliary contact fitted by user.
Actuator color	Other
Actuator type	Other
Connection type	Vertical
Degree of protection	NEMA Other
Degree of protection (front side)	IP20
Lifespan, mechanical	10,000 Operations
Mounting method	Surface mounting
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	Main switch Switch-disconnector
Rated impulse withstand voltage (Uimp)	6000 V
Safety parameter (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
Suitable for	Distribution board installation Ground mounting
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Ambient storage temperature - min	-30 °C
Ambient storage temperature - max	80 °C
Terminal capacity	6 - 70 mm ² , flexible with ferrules to DIN 46228

Stripping length (main cable)		21 mm
Tightening torque		7 Nm, Screw terminals
Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)		480 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)		520 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)		352 A
Rated insulation voltage (Ui)		1000 V
Rated operational current (Ie) at AC-21, 400 V, 415 V		125 A
Rated operational current (Ie) at AC-21, 500 V		125 A
Rated operational current (Ie) at AC-21, 690 V		125 A
Rated operational current (Ie) at AC-22, 380 V, 400 V, 415 V		125 A
Rated operational current (Ie) at AC-22, 500 V		125 A
Rated operational current (Ie) at AC-22, 690 V		125 A
Rated operational current (Ie) at AC-23A, 400 V, 415 V		125 A
Rated operational current (Ie) at AC-23A, 500 V		66 A
Rated operational current (Ie) at AC-23A, 690 V		42 A
Rated operational power at AC-23A, 400 V, 50 Hz		30 kW
Rated operational power at AC-23A, 500 V, 50 Hz		45 kW
Rated operational power at AC-23A, 690 V, 50 Hz		37 kW
Rated operational power at AC-3, 380/400 V, 50 Hz		0 kW
Rated operational voltage (Ue) at AC - max		690 V
Rated operational voltage (Ue) at AC - min		690 V
Rated uninterrupted current (Iu)		125 A
Uninterrupted current		Rated uninterrupted current Iu is specified for max. cross-section.
Breaking current		14.5 kA
Let-through energy		Max. 140 kA²s
Rated conditional short-circuit current (Iq)		50 kA
Rated short-time withstand current (Icw)		2,5 kA, Contacts, 1 second 2.5 kA
Short-circuit protection rating		125, Fuse, Contacts
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		4.5 W
Rated operational current for specified heat dissipation (In)		125 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013])			
Version as main switch			Yes
Version as maintenance-/service switch			Yes
Version as safety switch			No
Version as emergency stop installation			No
Version as reversing switch			No
Number of switches			1
Max. rated operation voltage Ue AC		V	690
Rated operating voltage		V	690 - 690
Rated permanent current Iu		A	125
Rated permanent current at AC-23, 400 V		A	66
Rated permanent current at AC-21, 400 V		A	125
Rated operation power at AC-3, 400 V		kW	0
Rated short-time withstand current Icw		kA	2.5
Rated operation power at AC-23, 400 V		kW	30
Switching power at 400 V		kW	0
Conditioned rated short-circuit current Iq		kA	50
Number of poles			4
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
Motor drive optional			No
Motor drive integrated			No
Voltage release optional			No
Device construction			Built-in device fixed built-in technique
Suitable for floor mounting			Yes
Suitable for front mounting 4-hole			No
Suitable for front mounting centre			No
Suitable for distribution board installation			Yes
Suitable for intermediate mounting			No
Colour control element			Other
Type of control element			Other
Interlockable			No
Type of electrical connection of main circuit			Screw connection
Degree of protection (IP), front side			IP20
Degree of protection (NEMA)			Other