

Switch-disconnector, DMM, 125 A, 3 pole, with blue knob, in CI-K5 enclosure
Part no. **DMM-125/3/I5/P-B**
 172849

Product name			Eaton DMM Switch-disconnector
Part no.			DMM-125/3/I5/P-B
EAN			4015081694631
Product Length/Depth			280 millimetre
Product height			160 millimetre
Product width			200 millimetre
Product weight			2.45 kilogram
Certifications			VDE 0660 IEC/EN 60947-3 RoHS IEC/EN 60947 KEMA CE EAC IEC/EN 60204 Lloyds
Product Tradename			DMM
Product Type			Switch-disconnector
Product Sub Type			None
Globally Marketable			Yes
			1 padlock, # 5 mm in CI-K5 enclosure Rated Short-time Withstand Current (Icw) for a time of 1 second
Features			Version as maintenance-/service switch Version as main switch
Fitted with:			Blue knob
Functions			Interlockable
Locking facility			Lockable in the 0 (Off) position
Number of poles			Three-pole
Accessories			Auxiliary contact fitted by user.
Degree of protection			NEMA 12
Degree of protection (front side)			IP65
Lifespan, mechanical			10,000 Operations
Mounting method			Surface mounting
Mounting position			As required
Overvoltage category			III
Pollution degree			3
Rated impulse withstand voltage (Uimp)			6000 V
Safety parameter (EN ISO 13849-1)			B10d values as per EN ISO 13849-1, table C.1
Suitable for			Ground mounting
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			40 °C
Ambient storage temperature - min			-40 °C
Ambient storage temperature - max			80 °C
Terminal capacity			6 - 70 mm ² , flexible with ferrules to DIN 46228
Stripping length (main cable)			21 mm
Tightening torque			7 Nm, Screw terminals

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)		1000 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)		528 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)		336 A
Rated insulation voltage (Ui)		1000 V
Rated operational current (Ie) at AC-21, 400 V, 415 V		125 A
Rated operational current (Ie) at AC-21, 500 V		125 A
Rated operational current (Ie) at AC-21, 690 V		125 A
Rated operational current (Ie) at AC-22, 380 V, 400 V, 415 V		125 A
Rated operational current (Ie) at AC-22, 500 V		125 A
Rated operational current (Ie) at AC-22, 690 V		125 A
Rated operational current (Ie) at AC-23A, 400 V, 415 V		125 A
Rated operational current (Ie) at AC-23A, 500 V		66 A
Rated operational current (Ie) at AC-23A, 690 V		42 A
Rated operational power at AC-23A, 400 V, 50 Hz		59 kW
Rated operational power at AC-23A, 500 V, 50 Hz		45 kW
Rated operational power at AC-23A, 690 V, 50 Hz		37 kW
Rated operational power at AC-3, 380/400 V, 50 Hz		0 kW
Rated operational voltage (Ue) at AC - min		690 V
Rated operational voltage (Ue) at AC - max		690 V
Rated uninterrupted current (Iu)		125 A
Uninterrupted current		Rated uninterrupted current Iu is specified for max. cross-section.
Breaking current		13.7 kA
Let-through energy		Max. 134 kA ² s
Rated conditional short-circuit current (Iq)		50 kA 30 kA at 415 V
Rated short-time withstand current (Icw)		2.5 kA 2,5 kA, Contacts, 1 second
Short-circuit protection rating		125, Fuse, Contacts
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Actuator color		Other
Actuator type		Short thumb-grip
Equipment heat dissipation, current-dependent Pvid		4.9 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		4.5 W
Rated operational current for specified heat dissipation (In)		125 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		UV resistance only in connection with protective shield.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013])		
Version as main switch		Yes
Version as maintenance-/service switch		Yes
Version as safety switch		No
Version as emergency stop installation		No
Version as reversing switch		No
Number of switches		1
Max. rated operation voltage Ue AC	V	690
Rated operating voltage	V	690 - 690
Rated permanent current Iu	A	125
Rated permanent current at AC-23, 400 V	A	66
Rated permanent current at AC-21, 400 V	A	125
Rated operation power at AC-3, 400 V	kW	0
Rated short-time withstand current Icw	kA	2.5
Rated operation power at AC-23, 400 V	kW	59
Switching power at 400 V	kW	0
Conditioned rated short-circuit current Iq	kA	50
Number of poles		3
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
Motor drive optional		No
Motor drive integrated		No
Voltage release optional		No
Device construction		Complete device in housing
Suitable for floor mounting		Yes
Suitable for front mounting 4-hole		No
Suitable for front mounting centre		No
Suitable for distribution board installation		No
Suitable for intermediate mounting		No
Colour control element		Other
Type of control element		Short thumb-grip
Interlockable		Yes
Type of electrical connection of main circuit		Screw connection
Degree of protection (IP), front side		IP65
Degree of protection (NEMA)		12