



Fuse-link, LV, 300 A, AC 500 V, NH2, gL/gG, IEC, dual indicator, live gripping lugs

**EL Number
(Norway)**

**300NHG2B
1664071**

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		300NHG2B
EAN		5027590475884
Product Length/Depth		150 millimetre
Product height		71 millimetre
Product width		54 millimetre
Product weight		651 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-2 DIN 43620 IEC 60269-1
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Globally Marketable		Yes

Amperage Rating		300 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL

Fuse size		NH2
Insulated metal gripping lugs (IMGL)		No

Suitable for		SD2-D Single pole NH Fuse base TD2-D Tripe pole NH Fuse base Microswitch 170H0235 Microswitch 170H0236 EBH Size 00 to 4 Horizontal fuse switch-disconnectors
--------------	--	--

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 [AFZ800015])

Fuse construction type according to IEC 60269		NH2
Voltage type		AC
Rated current	A	300
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	20