

Auxiliary contact module, 1 pole, Ith= 16 A, 1 N/O, Side mounted, Push in terminals, DILA, DILM7 - DILM15



**Part no. DILA-XHI10-S-PI
199323**

Product name	Eaton Moeller® series DILA Accessory Auxiliary contact module
Part no.	DILA-XHI10-S-PI
EAN	4015081974078
Product Length/Depth	47 millimetre
Product height	72 millimetre
Product width	16 millimetre
Product weight	0.02 kilogram
Certifications	IEC/EN 60947 VDE 0660 CSA Class No.: 3211-03 CSA CSA File No.: 012528 UL UL 508 UL File No.: E29184 CSA-C22.2 No. 14-05 CE marking UL Category Control No.: NKCR
Product Tradename	DILA
Product Type	Accessory
Product Sub Type	Auxiliary contact module
Catalog Notes	Auxiliary contacts used as mirror contacts (according to IEC/EN 60947-4-1 Appendix F (not N/C late open)) Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32 Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.
Features	Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)
Functions	For standard applications
Fitted with:	Interlocked opposing contacts
Number of poles	Single-pole
Electric connection type	Spring clamp connection
Degree of protection	IP20
Lifespan, electrical	1,300,000 Operations (at 230 V, AC-15, 3 A)
Model	Top mounting
Mounting method	Side mounting
Overvoltage category	III
Pollution degree	3
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	6000 V AC
Type	Side-mounting auxiliary contacts
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Ambient operating temperature (enclosed) - min	25 °C
Ambient operating temperature (enclosed) - max	40 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	80 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Terminal capacity (flexible with ferrule)			1 x (0.5 - 1.5) mm ² 1 x (0.5 - 2.5) mm ² 2 x (0.5 - 2.5) mm ² , Push-in terminals, ferrule to DIN 46228-1 1 x (0.5 - 1.5) mm ² , Push-in terminals, ferrule to DIN 46228-4
Terminal capacity (flexible)			1 x (0.5 - 2.5) mm ² 2 x (0.5 - 2.5) mm ²
Terminal capacity (solid)			1 x (0.5 - 0.25) mm ² 2 x (0.5 - 2.5) mm ² , Control circuit cables
Terminal capacity (solid/stranded AWG)			20 - 14
Conventional thermal current I_{th} at 60°C (3-pole, open)			16 A
Conventional thermal current I_{th} of auxiliary contacts (1-pole, open)			0.1 A
Rated operational current (I_e)			10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series) 6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series) 1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)
Rated operational current (I_e) at AC-15, 220 V, 230 V, 240 V			4 A
Rated operational current (I_e) at AC-15, 380 V, 400 V, 415 V			4 A
Rated operational current (I_e) at AC-15, 500 V			1.5 A
Rated operational current (I_e) at DC-13, 24 V			2.5 A
Rated operational current (I_e) at DC-13, 60 V			1 A
Rated operational current (I_e) at DC-13, 110 V			0.5 A
Rated operational current (I_e) at DC-13, 220 V, 230 V			0.25 A
Rated insulation voltage (U_i)			690 V
Rated operational voltage (U_e) at AC - max			500 V
Short-circuit protection rating without welding			10 A gG/gL, 500 V, Max. Fuse, Contacts
Safe isolation			400 V AC, Between auxiliary contacts, According to EN 61140 400 V AC, Between coil and auxiliary contacts, According to EN 61140
Switching capacity (auxiliary contacts, general use)			10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)			A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
Connection type			Push in terminals
Control circuit reliability			< 2 λ, < 1 failure at 100,000,000 Operations (at $U_{#} = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
Number of contacts (change-over contacts)			0
Number of contacts (normally closed contacts)			0
Number of contacts (normally open contacts)			1

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ec1@ss10.0.1-27-37-13-02 [AKN342013])			
Number of contacts as change-over contact			0
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			0
Number of fault-signal switches			0
Rated operation current I_e at AC-15, 230 V		A	4
Type of electric connection			Spring clamp connection
Model			Top mounting
Mounting method			Side mounting
Lamp holder			None