



XEP3S1W3B529 (43 542 94)

Microbr.armrustfriplastrulle



[Last ned produktdatablad for XEP3S1W3B529](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dimensions Drawings](#) | [Connections and Schema](#) | [Technical Description](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

 Skjul

Produktspekter	OsiSense XC
Serie navn	Special format
Produkt eller komponent type	Microswitch
Kortnavn utstyr	XEP3
Type føler	Miniature, DIN 41635 A format
Hode type	Plunger head
Lever material	Glass reinforced polyamide roller Rustfritt stål
Lever fixing position	B
Bevegelse av hode	Linjær
Type arm/stempel	Roller lever
Bryter påvirkning	Horrisontal
Tilnærmings type	Lateral approach
Elektrisk tilkobling	6,35 mm kabelklips pinne
Kontakttype og sammensetning	1 C/O standard
Driftsområde kontakter	Momentan
Kontaktmateriale	AgNi

Komplementær

 Skjul

Materiale kropp	Polyester
Maximum force for tripping	0.2 N lever fixing position in A 0.4 N lever fixing position in B 0.53 N lever fixing position in C
Minimum release force	0.05 N lever fixing position in A 0.1 N lever fixing position in B 0.13 N lever fixing position in C
Maximum permanent end of travel force	10 N lever fixing position in B 13 N lever fixing position in C 5 N lever fixing position in A
Tripping point	20.5 mm lever fixing position in A 20.5 mm lever fixing position in B 20.5 mm lever fixing position in C
Maximum differential travel	0.53 mm lever fixing position in C 0.7 mm lever fixing position in B 1.4 mm lever fixing position in A
Minimum over travel	1.8 mm lever fixing position in C 2.4 mm lever fixing position in B 4.8 mm lever fixing position in A
Inter contact distance	0.4 mm
Kontakt angivelse	B300; AC-15(Ue = 240 V, Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A R300; DC-13(Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A
[Ith] fri luft termisk strøm	15 A på 250 V 50/60 Hz
Mekanisk levetid	20000000 sykluser
Bredde	10 mm
Høyde	16 mm
Dybde	28 mm
Vekt	6.6 g
Klemmebeskrivelse ISO n°1	(1-2-4)OC

Miljø

 Skjul

IP-grad	IP40
Omgivelsestemperatur drift	-25...125 °C
Merking	CE
Standarder	CURus EN 60947-5-1 EN 61058 IEC 60947-5-1 UL 1054

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0549 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering