



XEP3S1W3 (43 542 96)

Microswitch stempel C/O



[Last ned produktdatablad for XEP3S1W3](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

[Karakteristikk](#) | [Dimensions Drawings](#) | [Connections and Schema](#) | [Technical Description](#) | [Dokumenter og nedlastning](#)

Finn andre produkter og tilbehør



Finn ditt Schneider Electric verktøy

Teknisk informasjon

 Skjul

Produktspekter	OsiSense XC
Serie navn	Special format
Produkt eller komponent type	Microswitch
Kortnavn utstyr	XEP3
Type føler	Miniature, DIN 41635 A format
Hode type	Plunger head
Bevegelse av hode	Linjær
Type arm/stempel	Plunger
Bryter påvirkning	On end
Tilnærmings type	Vertical approach
Elektrisk tilkobling	6,35 mm kabelklips pinne
Kontakttype og sammensetning	1 C/O standard
Driftsområde kontakter	Momentan
Kontaktmateriale	AgNi

Komplementær

 Skjul

Materiale kropp	Polyester
Maximum force for tripping	0.8 N lever fixing position in A 0.8 N lever fixing position in B 0.8 N lever fixing position in C
Minimum release force	0.2 N lever fixing position in A 0.2 N lever fixing position in B 0.2 N lever fixing position in C
Maximum permanent end of travel force	20 N lever fixing position in A 20 N lever fixing position in B 20 N lever fixing position in C
Tripping point	14.7 mm lever fixing position in A 14.7 mm lever fixing position in B 14.7 mm lever fixing position in C
Maximum differential travel	0.35 mm lever fixing position in A 0.35 mm lever fixing position in B 0.35 mm lever fixing position in C
Minimum over travel	1.2 mm lever fixing position in A 1.2 mm lever fixing position in B 1.2 mm lever fixing position in C
Inter contact distance	0.4 mm
Kontakt angivelse	B300; AC-15(Ue = 240 V, Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A R300; DC-13(Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A
[Ith] fri luft termisk strøm	15 A på 250 V 50/60 Hz
Mekanisk levetid	20000000 sykluser
Bredde	10 mm
Høyde	16 mm
Dybde	28 mm
Vekt	5.6 g
Klemmebeskrivelse ISO n°1	(1-2-4)OC

Miljø Skjul

IP-grad	IP40
Omgivelsestemperatur drift	-25...125 °C
Merking	CE
Standarder	CURus EN 60947-5-1 EN 61058 IEC 60947-5-1 UL 1054

Bærekraftig Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0549 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering