

## Mounting rail vertical

Part no. **EPTV65**  
**143837**

|                                    |  |                                     |
|------------------------------------|--|-------------------------------------|
| <b>General specifications</b>      |  |                                     |
| Product name                       |  | Eaton xEnergy Basic other accessory |
| Part no.                           |  | EPTV65                              |
| EAN                                |  | 4015081403714                       |
| Product Length/Depth               |  | 25 millimetre                       |
| Product height                     |  | 65 millimetre                       |
| Product width                      |  | 16 millimetre                       |
| Product weight                     |  | 0.053 kilogram                      |
| Product Tradename                  |  | xEnergy Basic                       |
| Product Type                       |  | Accessories                         |
| Product Sub Type                   |  | Other                               |
| <b>Delivery program</b>            |  |                                     |
| Model                              |  | Singular profile                    |
| Color                              |  | Other                               |
| <b>Technical Data - Mechanical</b> |  |                                     |
| Surface protection                 |  | Galvanic/electrolytic zinc plated   |
| Material                           |  | Steel                               |
| Material thickness                 |  | 2 mm                                |
| Load bearing capacity              |  | 0 kN                                |
| Area of inertia Iz                 |  | 0                                   |
| Hole width                         |  | 3.6 mm                              |
| Moment of resistance Wy            |  | 0 cm <sup>3</sup>                   |
| Moment of resistance Wz            |  | 0 cm <sup>3</sup>                   |
| Perforation type                   |  | 3 sides punched                     |
| Profile shape                      |  | U-profile                           |
| Slit width                         |  | 9.5 mm                              |
| <b>Additional information</b>      |  |                                     |
| RAL-number                         |  | 0                                   |

## Technical data ETIM 8.0

|                                                                                                                                                                                                 |                 |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------------|
| Fasteners (EG000049) / Mounting rail/-profile (EC000386)                                                                                                                                        |                 |                  |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Cable carrier system / Shank/profile bar (ec1@ss10.0.1-27-40-05-01 [AC0321012]) |                 |                  |
| Length                                                                                                                                                                                          | mm              | 25               |
| Width                                                                                                                                                                                           | mm              | 16               |
| Height                                                                                                                                                                                          | mm              | 65               |
| Slit width                                                                                                                                                                                      | mm              | 9.5              |
| Material thickness                                                                                                                                                                              | mm              | 2                |
| Profile shape                                                                                                                                                                                   |                 | U-profile        |
| Model                                                                                                                                                                                           |                 | Singular profile |
| Type of perforation                                                                                                                                                                             |                 | 3 sides punched  |
| Hole width                                                                                                                                                                                      | mm              | 3.6              |
| With toothing                                                                                                                                                                                   |                 | No               |
| Snap-off                                                                                                                                                                                        |                 | No               |
| Load bearing capacity                                                                                                                                                                           | kN              | 0                |
| Area moment of inertia Iy                                                                                                                                                                       | cm <sup>4</sup> | 0                |
| Area of inertia Iz                                                                                                                                                                              | cm <sup>4</sup> | 0                |
| Moment of resistance Wy                                                                                                                                                                         | cm <sup>3</sup> | 0                |
| Moment of resistance Wz                                                                                                                                                                         | cm <sup>3</sup> | 0                |

|                                    |    |                                   |
|------------------------------------|----|-----------------------------------|
| Suitable for circuit integrity     |    | No                                |
| Material                           |    | Steel                             |
| Material quality                   |    | Other                             |
| Surface protection                 |    | Galvanic/electrolytic zinc plated |
| Layer thickness surface protection | µm |                                   |
| Colour                             |    | Other                             |
| RAL-number                         |    | 0                                 |
| Weight                             | kg | 0.053                             |