

## Mounting rail connector

Part no. **EPTV-E**  
**143861**

|                                     |  |                                     |
|-------------------------------------|--|-------------------------------------|
| <b>General specifications</b>       |  |                                     |
| Product name                        |  | Eaton xEnergy Basic other accessory |
| Part no.                            |  | EPTV-E                              |
| EAN                                 |  | 4015081403950                       |
| Product Length/Depth                |  | 44 millimetre                       |
| Product height                      |  | 64 millimetre                       |
| Product width                       |  | 28.5 millimetre                     |
| Product weight                      |  | 0.13 kilogram                       |
| Compliances                         |  | RoHS conform                        |
| Product Tradename                   |  | xEnergy Basic                       |
| Product Type                        |  | Accessories                         |
| Product Sub Type                    |  | Other                               |
| <b>Delivery program</b>             |  |                                     |
| Model                               |  | Singular profile                    |
| Color                               |  | Other                               |
| <b>Technical Data - Mechanical</b>  |  |                                     |
| Surface protection                  |  | Other                               |
| Material                            |  | Other                               |
| Material thickness                  |  | 11 mm                               |
| Load bearing capacity               |  | 0 kN                                |
| Area of inertia I <sub>z</sub>      |  | 0                                   |
| Hole width                          |  | 0 mm                                |
| Moment of resistance W <sub>y</sub> |  | 0 cm <sup>3</sup>                   |
| Moment of resistance W <sub>z</sub> |  | 0 cm <sup>3</sup>                   |
| Perforation type                    |  | None                                |
| Profile shape                       |  | Other                               |
| Slit width                          |  | 0 mm                                |
| <b>Additional information</b>       |  |                                     |
| RAL-number                          |  | 0                                   |

**Technical data ETIM 8.0**

|                                                                                                                                                                                                 |                 |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------------|
| Fasteners (EG000049) / Mounting rail/-profile (EC000386)                                                                                                                                        |                 |                  |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Cable carrier system / Shank/profile bar (ec1@ss10.0.1-27-40-05-01 [AC0321012]) |                 |                  |
| Length                                                                                                                                                                                          | mm              | 44               |
| Width                                                                                                                                                                                           | mm              | 28.5             |
| Height                                                                                                                                                                                          | mm              | 64               |
| Slit width                                                                                                                                                                                      | mm              | 0                |
| Material thickness                                                                                                                                                                              | mm              | 11               |
| Profile shape                                                                                                                                                                                   |                 | Other            |
| Model                                                                                                                                                                                           |                 | Singular profile |
| Type of perforation                                                                                                                                                                             |                 | None             |
| Hole width                                                                                                                                                                                      | mm              | 0                |
| With toothing                                                                                                                                                                                   |                 | No               |
| Snap-off                                                                                                                                                                                        |                 | No               |
| Load bearing capacity                                                                                                                                                                           | kN              | 0                |
| Area moment of inertia I <sub>y</sub>                                                                                                                                                           | cm <sup>4</sup> | 0                |
| Area of inertia I <sub>z</sub>                                                                                                                                                                  | cm <sup>4</sup> | 0                |
| Moment of resistance W <sub>y</sub>                                                                                                                                                             | cm <sup>3</sup> | 0                |

|                                    |  |     |       |
|------------------------------------|--|-----|-------|
| Moment of resistance Wz            |  | cm³ | 0     |
| Suitable for circuit integrity     |  |     | No    |
| Material                           |  |     | Other |
| Material quality                   |  |     | Other |
| Surface protection                 |  |     | Other |
| Layer thickness surface protection |  | µm  |       |
| Colour                             |  |     | Other |
| RAL-number                         |  |     | 0     |
| Weight                             |  | kg  | 0.13  |