



SPV040

Cartridge T2 1P photovoltaic +/- for SPV340

Technical properties

Configuration

Number of modules	1
-------------------	---

Controls and indicators

Indicator lamp	Optic
----------------	-------

Main electrical features

Rated operational voltage Ue	1000 V
Nominal discharge current (In) 8/20μs, IEC 61643)L-N(PEN)/ N-PE	15 kA

Voltage

Maximum continuous operating voltage Uc	585 V
Voltage protection level Up according to IEC61643-1	1.9 kV
Voltage protection level Up L-PE/N-PE according to IEC61643-11	1.9 kV
Voltage level Up L-N/PEN IEC61643-11	1.9 kV

Electric current

Max discharge (Imax) L-N(PEN)/ N-PE	40 kA
-------------------------------------	-------

Dimensions

Depth of installed product	43.4 mm
Height of installed product	52.4 mm
Width of installed product	17.5 mm

Electrical specifications

Short-circuit breaking capacity (Iscrr)	2000 A
---	--------

Installation, mounting

Tightening torque	3
-------------------	---

Connection

Connection cross-section of input and output with screws, for massive conductors	35 mm ²
Connection cross section of access and exit with screws, for flexible conductor	25 mm ²

Standards

Approvals	KEMA, CMIM
Test class IEC61643-11 / VDE0675-6-11	T2
European directive WEEE	concerned

Use conditions

Operating temperature -40...80 °C

Identification

meta_keyword Surge protector;Modular;Surge protectors;Surge suppressors;Electronic lightning rods;Devices for protection against surges;Surge protectors.