



### Hovedkarakteristikk

|                              |                                 |
|------------------------------|---------------------------------|
| Produkt eller komponent type | Cartridge                       |
| Kortnavn utstyr              | C8-350                          |
| Overspenningsvern type       | Electrical distribution network |

### Alternativer

|                                           |                                  |
|-------------------------------------------|----------------------------------|
| Surge arrester class type                 | Type 2                           |
| Surge arrester technology                 | MOV                              |
| Jordingssystem                            | TN<br>TT                         |
| [Ue] merkespenning                        | 230 V AC 50 Hz                   |
| Nominal discharge current                 | 2.5 kA                           |
| Maximum discharge current                 | 8 kA                             |
| [Uc] maksimal kontinuerlig driftsspenning | 350 V                            |
| [Opp] overspenningsvern nivå              | 1.1 kV type 2                    |
| Lokal varsling                            | Flag color: Hvit/rød             |
| Monteringsmetode                          | Plugg inn                        |
| Montering                                 | Inn i SPD modul                  |
| 9 mm polbredde                            | 1.3                              |
| Høyde                                     | 50 mm                            |
| Bredde                                    | 12 mm                            |
| Dybde                                     | 57 mm                            |
| Farge                                     | Hvit ( RAL 9003 )                |
| Materiale                                 | PBT (polybutylene terephthalate) |
| Response tid                              | < 25 ns                          |

### Miljø

|                                  |                            |
|----------------------------------|----------------------------|
| standarder                       | EN 61643-11<br>IEC 61643-1 |
| produktsertifikater              | KEMA-KEUR<br>NF            |
| IP-grad                          | Forside: IP20              |
| relativ fuktighet                | 5...90 %                   |
| operating altitude               | 0...2000 m                 |
| omgivelsestemperatur drift       | -25...60 °C                |
| omgivelsestemperatur for lagring | -40...70 °C                |

### Bærekraftig

|                        |                                                                       |
|------------------------|-----------------------------------------------------------------------|
| Bærekraftig            | Green Premium produkt                                                 |
| RoHS (datokode: YYWW)  | Compliant - since 1742 - Schneider Electric declaration of conformity |
| REACH                  | Reference not containing SVHC above the threshold                     |
| Produktets miljøprofil | Tilgjengelig                                                          |

