## **Product Information Sheet**

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources   |                                  |                           | ora with regard to energ   | B) 1440-1111-16 01 118110 |
|---|----------------------------------|---------------------------|--|---------------------------|
| Supplier's name   | or trade mark:                   | LEDVANCE                  |  |                           |
| Supplier's addres   | ss: LEDVANCE G                   | imbH, Parkring 29-3       | 3, 85748 Garching, DE  |                           |
| Model identifier:   | : AC42562                        |                           |  |                           |
| Type of light sou   | rce:                             |                           |  |                           |
| Lighting technology used:   |                                  | LED                       | Non-directional or directional:  | NDLS                      |
| Light source cap-type   |                                  | G13                       |  |                           |
| (or other electric  | interface)                       |                           |  |                           |
| Mains or non-mains:   |                                  | NMLS                      | Connected light source (CLS):  | No                        |
| Colour-tuneable light source:   |                                  | No                        | Envelope:  | -                         |
| High luminance light source:  |                                  | No                        |  |                           |
| Anti-glare shield:  |                                  | No                        | Dimmable:  | No                        |
|   |                                  | Product para              |  |                           |
| Parameter   |                                  | Value                     | Parameter  | Value                     |
|   |                                  | General product p         | arameters:   |                           |
| Energy consum mode (kWh/100 up to the nearest   | 0 h), rounded                    | 14                        | Energy efficiency class  | D                         |
| Useful luminous dicating if it refer a sphere (360º), (120º) or in a nar                              | rs to the flux in in a wide cone | 2 100 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000                     |
| On-mode power (P <sub>on</sub> ), ex-<br>pressed in W   |                                  | 14,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00                      |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal |                                  | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80                        |
|   | Height<br>Width                  | 1 211<br>28               | Spectral power distribution in the   | See image<br>in last page |

28

range 250 nm to 800

nm, at full-load

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |                              |       |  |  |  |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |  |  |  |
|  |      | Chromaticity coordi-         | 0,382 |  |  |  |
|  |      | nates (x and y)              | 0,380 |  |  |  |
| Parameters for LED and OLED light sources:                                 |      |                              |       |  |  |  |
| R9 colour rendering index value  | 0    | Survival factor              | 0,90  |  |  |  |
| the lumen maintenance factor   | 0,70 |                              |       |  |  |  |

(a)'-': not applicable; (b)'-': not applicable;

