## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or trade mark:	LEDVANCE
------------	------	----------------	----------

Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE

Model identifier: AC44835

_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	SOUI	LC.

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		constant cur-		
(or other electric interface)		rent: 370 mA		
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para	meters	ı
Parameter		Value	Parameter	Value
		General product p	parameters:	1
Energy consur mode (kWh/10 up to the neares	• •	62	Energy efficiency class	D
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		9 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), ex- pressed in W		62,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	70
Outer dimen-	Height	127	Spectral power dis-	See image
		-	<b>⊣</b>	

tribution

range 250 nm to 800

nm, at full-load

39

2

in the

in last page

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,440		
		nates (x and y)	0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	60	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

