

NH switch-disconnectors mounting unit, 400A, W=800mm, XNH2 3p, mounting on mounting plate



Part no. BPZ-XNH2X-3/X-800-MV  
184556  
EL Number 2456359  
(Norway)

|                                      |  |  |                                     |
|--------------------------------------|--|--|-------------------------------------|
| General specifications               |  |  |                                     |
| Product name                         |  |  | Eaton xEnergy Basic other accessory |
| Part no.                             |  |  | BPZ-XNH2X-3/X-800-MV                |
| EAN                                  |  |  | 4015081785957                       |
| Product Length/Depth                 |  |  | 80 millimetre                       |
| Product height                       |  |  | 455 millimetre                      |
| Product width                        |  |  | 725 millimetre                      |
| Product weight                       |  |  | 5.5 kilogram                        |
| Compliances                          |  |  | RoHS conform                        |
| Product Tradename                    |  |  | xEnergy Basic                       |
| Product Type                         |  |  | Accessories                         |
| Product Sub Type                     |  |  | Other                               |
| Delivery program                     |  |  |                                     |
| Amperage rating                      |  |  | 400 A                               |
| Number of poles                      |  |  | Three-pole                          |
| Technical Data - Mechanical          |  |  |                                     |
| Frame                                |  |  | NH2                                 |
| Mounting method                      |  |  | Mounting plate                      |
| Number of fuse holders (knife blade) |  |  | 3                                   |
| Number of fuse switch disconnectors  |  |  | 3                                   |
| Additional information               |  |  |                                     |
| Fitted with:                         |  |  | Cover                               |

Technical data ETIM 8.0

|                                                                                                                                                                                                                                       |  |    |                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|----------------|
| Energy distribution systems (EG000015) / Distributor assembly Low Voltage HRC fuse systems (EC002286)                                                                                                                                 |  |    |                |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly Low Voltage HRC fuse systems (ecl@ss10.0.1-27-40-06-19 [ACO401011]) |  |    |                |
| Number of poles                                                                                                                                                                                                                       |  |    | 3              |
| Number of knife blade fuse holders                                                                                                                                                                                                    |  |    | 3              |
| Number of fuse switch disconnectors                                                                                                                                                                                                   |  |    | 3              |
| Concurrently switching neutral conductor                                                                                                                                                                                              |  |    | No             |
| Rated current                                                                                                                                                                                                                         |  | A  | 400            |
| Mounting method                                                                                                                                                                                                                       |  |    | Mounting plate |
| Construction size                                                                                                                                                                                                                     |  |    | NH2            |
| With cover                                                                                                                                                                                                                            |  |    | Yes            |
| Height                                                                                                                                                                                                                                |  | mm | 455            |
| Width                                                                                                                                                                                                                                 |  | mm | 725            |
| Depth                                                                                                                                                                                                                                 |  | mm | 80             |