



XEFFECT CI
014286


Overview


Specifications


Resources

How to



014286

Eaton xEffect Ci Enclosures Switch- & Controlgear
smoky gray, HxWxD=250x187.5x25mm, NA model

Discover the xEffect Ci models



GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME Eaton xEffect Ci Enclosures Switch- & Controlgear

CATALOG NUMBER 014286

Product specifications



MODEL CODE D125-CI23-NA

EAN 4015080142867

PRODUCT LENGTH/DEPTH 65 mm

PRODUCT HEIGHT 250 mm

PRODUCT WIDTH 188 mm

PRODUCT WEIGHT 0.301 kg

COMPLIANCES RoHS conform

PRODUCT SPECIFICATIONS

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
ACCESSORY/SPARE PART TYPE	Enclosure cover NA
RAL-NUMBER	0
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH	0 mm
SUITABLE FOR	Outdoor set-up
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
SURFACE FINISHING	Untreated
10.2.5 LIFTING	5 kg per enclosure with support frame and lifting aid secured as per the latest applicable instruction leaflet
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	13 W
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	850 °C; meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	U _i = 1000 V AC
DEGREE OF PROTECTION	IP65
SPECIAL FEATURES	Sealable cover fasteners
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	7 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	6 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	14 W
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
COLOR	Other
UNIT TYPE	Modular system
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	13 W
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi

MATERIAL	Plastic
FUNCTIONS	Basic enclosure
MOUNTING DEPTH	125 mm
10.9.3 IMPULSE WITHSTAND VOLTAGE	8 kV
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	7 W
TYPE	• Basic enclosure • Enclosure cover for North America • xEnergy Safety Ci
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
SUITABLE FOR ENCLOSURE BUILDING WIDTH	0 mm
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Protection class 2, therefore not applicable.
USED WITH	U-CI23... Basic enclosure Enclosure cover for North America xEnergy Safety Ci
COVER/DOOR TYPE	Transparent, smoky gray
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.6 MECHANICAL IMPACT	IK10
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP65, with base unit

Brochures

Certification reports

Installation videos



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.