




XENERGY SAFETY CI
027019


Overview


Specifications


Resources


How to



027019

Eaton xEnergy Safety Ci LV systems LV switchgear
top+bottom open, HxWxD=250x375x225mm

Access the Online Catalog



GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME Eaton xEnergy Safety Ci empty enclosure insulated

CATALOG NUMBER 027019

Product specifications



MODEL CODE CI43-200

EAN 4015080270195

PRODUCT LENGTH/DEPTH 225 mm

PRODUCT HEIGHT 250 mm

PRODUCT WIDTH 375 mm

PRODUCT WEIGHT 2.203 kg

COMPLIANCES RoHS conform

CERTIFICATIONS EN 62208
EN 61439-2

PRODUCT SPECIFICATIONS

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
CIRCUIT INTEGRITY	Other
TEMPERATURE RESISTANCE	Temperature resistant: 80 °C (gasket) Temperature resistant: -40 °C - 120 °C (enclosure) Temperature resistant: 85 °C (enclosure bolt)
PLATE THICKNESS (COVER/DOOR)	6 mm
RAL-NUMBER	7035
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
PLATE THICKNESS (CABINET)	6 mm
MOUNTING METHOD	Surface mounted (plaster)
10.2.5 LIFTING	10 kg per enclosure with support frame and lifting aid and secured as per the latest applicable instruction leaflet
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
NUMBER OF OPENINGS (FLANGE PLATES)	4
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
CHEMICAL RESISTANCE	Resistant against: acids < 10 %, mineral oil, alcohol, salt solutions Partly resistant to: Acids > 10 % Not resistant to: alkalis, benzene
COVER/DOOR MODEL	Closed
INTERNAL DEPTH	200 mm
MOUNTING DEPTH WITH MOUNTING PLATE	200 mm
SPECIAL FEATURES	Housing prepared for distribution board Two sides closed or out two sides open Sealable cover fasteners Integrated mechanism for short-circuits
COLOR	Gray
UNIT TYPE	Single unit
BUILT-IN DEPTH	200 mm
FEATURES	UV resistance beneath protective shield Cover with overpressure release
10.9.3 IMPULSE WITHSTAND VOLTAGE	8 kV
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Protection class 2, therefore not applicable.
COVER/DOOR COLOR	7035

COVER/DOOR COLOR	Transparent
SURFACE PROTECTION	Other
COVER/DOOR TYPE	Transparent None Optional
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.6 MECHANICAL IMPACT	IK10
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP65
NOMINAL CURRENT	1600 A
FLAMMABILITY CHARACTERISTICS (UL)	V1 (base) (UL94) V2 (cover) (UL94)
SUITABLE FOR	Lightning protection Outdoor use
SURFACE FINISHING	Resistant to corrosion
NUMBER OF ROWS	0
PROTECTION CLASS	II
WIDTH IN NUMBER OF MODULAR SPACINGS	15
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	48 W
NUMBER OF CONDUIT INLETS	76
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Lower part: 960 °C / cover: 850 °C
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Ui = 1000 V AC
DEGREE OF PROTECTION	IP65 Other IK10
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	25 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	22 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	51 W
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	45 W

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
MATERIAL	Non-reinforced polycarbonate (cover) Halogen free Glass-fibre reinforced polycarbonate (base)
FUNCTIONS	Extension possible
AMBIENT OPERATING TEMPERATURE DETAILS	-40 °C - 80 °C
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	24 W
SALINE SPRAY RESISTANCE	IEC 60068-2-11
ENCLOSURE MATERIAL	Plastic
TYPE	Basic enclosure Panel enclosures xEnergy Safety Ci
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SURFACE TREATMENT	Resistant to corrosion
NUMBER OF MODULES	1

Brochures

Catalogs

Drawings

Installation instructions

mCAD model

027019



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.