




XENERGY SAFETY CI
044879


Overview


Specifications


Resources

How to



044879

Eaton xEnergy Safety Ci LV systems LV switchgear
rubber, IP54, HxWxD=116x329x23mm

Access the Online Catalog



GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME Eaton xEnergy Safety Ci flange plate

CATALOG NUMBER 044879

Product specifications



MODEL CODE FL4-D

EAN 4015080448792

PRODUCT LENGTH/DEPTH 115 mm

PRODUCT HEIGHT 23 mm

PRODUCT WIDTH 330 mm

PRODUCT WEIGHT 0.344 kg

COMPLIANCES RoHS conform

PRODUCT SPECIFICATIONS

ACCESSORY/SPARE PART TYPE	Sponge-rubber flange IP54
OUTER CABLE DIAMETER	2 x (20 - 30) mm 4 x (15 - 19) mm 42 x (10 - 13) mm
SHAPE	Straight
UNIT TYPE	Modular system
FEATURES	Pre-stamping
MATERIAL	Plastic
SUITABLE FOR NOMINAL THREAD (PG) - MIN	10
THICKNESS	4 mm
SUITABLE FOR CABLE DIAMETER - MAX	30 mm
TYPE	Accessory for basic enclosures Basic enclosure xEnc
NUMBER OF CONNECTOR HOLES	0
USED WITH	NY Y, NY M 4 x 10 mm ² - 4 x 50 mm ² NY Y, NY M 4 x 4 mm ² - 5 x 10 mm ² 375 mm (enclosure dimensions) NY Y, NY M 3 x 1.5 mm ² - 5 x 2.5 mm ² Accessory for basic enclosures Basic enclosure xEnergy Safety Ci
SURFACE PROTECTION	Untreated
MODEL	Cable screw gland
THREAD TYPE	None
SUITABLE FOR NOMINAL THREAD (PG) - MAX	30
DEGREE OF PROTECTION	IP54 Other
SUITABLE FOR CABLE DIAMETER - MIN	10 mm

Brochures

Catalogs

Drawings

Installation instructions

mCAD model

044879



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.