


RMQ TITAN MODULAR PILOT DEVICES
216422


Overview




Specifications



Resources

How to

**216422**

Eaton Moeller® series M22 Button plate, flat white

Contact me about this product



Photo is representative



General specifications

**GENERAL SPECIFICATIONS**

Product specifications

**PRODUCT NAME**

Eaton Moeller® series M22 Accessory Button plate

CATALOG NUMBER

216422

MODEL CODE

M22-XD-W

EAN

4015082164225

PRODUCT LENGTH/DEPTH

24 mm

PRODUCT HEIGHT

3 mm

PRODUCT WIDTH

24 mm

PRODUCT WEIGHT

0.002 kg

CERTIFICATIONS

UL/CSA certification not required

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	Accessories
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
INSCRIPTION TYPE	Blank
SHAPE	Round
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
SUITABLE FOR	Push button
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
OUTSIDE DIAMETER	22.5 mm
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
DESIGN	Flush
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
INSCRIPTION	Individual inscription possible: ≤ 5 characters: letter Individual inscription possible: > 5 characters: letter None
LANGUAGE	Other
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
CONSTRUCTION TYPE	Flat
PROGRAM DIAMETER	22 mm
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
COLOR	White
10.10 TEMPERATURE RISE	Not applicable.

CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
IMPRINT	Other
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
TYPE	Flat
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
IMPRINT ISO SYMBOLS	None
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
USED WITH	M22-DG-X M22(S)-D-X M22(S)-DR-X
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

mCAD model

Specifications and datasheets

System overview

216422



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.