




RMQ TITAN MODULAR PILOT DEVICES  
216433

  
Overview

  
Specifications

  
Resources

How to



216433

Eaton Moeller® series M22 Button plate, raised blue

Contact me about this product



GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME Eaton Moeller® series M22 Accessory Button plate

CATALOG NUMBER 216433

Product specifications



MODEL CODE M22-XDH-B

EAN 4015082164331

PRODUCT LENGTH/DEPTH 24 mm

PRODUCT HEIGHT 9 mm

PRODUCT WIDTH 24 mm

PRODUCT WEIGHT 1.6 g

CERTIFICATIONS UL/CSA certification not required

## PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	Accessories
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
INSCRIPTION TYPE	Blank
SHAPE	Round
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
SUITABLE FOR	Push button
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
OUTSIDE DIAMETER	22.5 mm
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
BEZEL	Silver
DESIGN	Extended
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
INSCRIPTION	Individual inscription possible: ≤ 5 characters: letter Individual inscription possible: > 5 characters: letter None
LANGUAGE	Other
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
CONSTRUCTION TYPE	High
PROGRAM DIAMETER	22 mm
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
COLOR	Blue

<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>IMPRINT</b>	Other
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to
<b>IMPRINT ISO SYMBOLS</b>	None
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the instruction leaflet (IL) is observed.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

## Installation videos

---

## mCAD model

---

## System overview

---

216433



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.