




RMQ TITAN MODULAR PILOT DEVICES
216496


Overview


Specifications


Resources

How to



216496


Eaton Moeller® series M22 Carrier, +label, ON M22

Contact me about this product




Designed to work together

Discover other Eaton products and accessories built to enhance this product.



198272

Eaton Moeller® series M22 Acoustic device, compact, IP40, Buzzer BA9s, 18-30V, pulsed tone



198271

Eaton Moeller® series M22 Acoustic device, compact, IP40, Buzzer BA9s. 18-30V DC, continuous tone

View more

View less

GENERAL SPECIFICATIONS

General specifications	>	PRODUCT NAME	Eaton Moeller® series M22 Accessory Legend hold
		CATALOG NUMBER	216496
Product specifications	>	MODEL CODE	M22S-ST-GB6
		EAN	4015082164966
		PRODUCT LENGTH/DEPTH	4 mm
		PRODUCT HEIGHT	50 mm
		PRODUCT WIDTH	30 mm
		PRODUCT WEIGHT	0.002 kg
		CERTIFICATIONS	UL/CSA certification not required

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
PRODUCT CATEGORY	Accessories
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
OPENING DIAMETER	22 mm
SHAPE	Rectangular
RAL-NUMBER	9005
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT P _{VID}	0 W
HEAT DISSIPATION CAPACITY P _{DISS}	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
DESIGN	Round
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
INSCRIPTION	ON " ON "
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST OF INSUL. MAT TO ABNORMAL	

MEETS REQUIREMENTS FOR RESISTANCE TO DEFORMATION HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP66
OPENING HEIGHT	0 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
COLOR	Black
10.10 TEMPERATURE RISE	Not applicable.
CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be considered.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be considered.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instructions in the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be considered.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be considered.
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

PEP Eco-passport

System overview

216496



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

