


RMQ TITAN MODULAR PILOT DEVICES
290260


Overview




Specifications



Resources

How to

**290260**

Eaton Moeller® series M22 Label, for 2 position sw

Contact me about this product

General specifications

**GENERAL SPECIFICATIONS**

Product specifications

**PRODUCT NAME**

Eaton Moeller® series M22 Accessory Label for 4-p

CATALOG NUMBER

290260

MODEL CODE

M22-XCK3

EAN

4015082902605

PRODUCT LENGTH/DEPTH

50 mm

PRODUCT HEIGHT

2 mm

PRODUCT WIDTH

50 mm

PRODUCT WEIGHT

0.004 kg

CERTIFICATIONS

UL/CSA certification not required

VDE 0660

IEC/EN 60947

DNV

GL

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	Accessories
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
SHAPE	Square
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
OUTSIDE DIAMETER	0 mm
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
INSCRIPTION	Other 2 direction arrows, can be turned through 90°
LANGUAGE	Other
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
COLOR	Silver
10.10 TEMPERATURE RISE	Not applicable.
CONNECTION TO SMARTWIRE-DT	No

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
IMPRINT ISO SYMBOLS	Symbol " arrow "
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
USED WITH	Two-position joystick M22-D4... M22-DI4... M22-WJ... M22-WRJ... M22S-WJ... M22S-WRJ...
MOUNTING POSITION	As required
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

mCAD model

System overview

290260



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.