

United States Select your location

Search parts, catalogs

Sign in

We make what matters work*

Products Digital Services Markets Support Company

Search

Toggle Mobile Menu

Search

Search

Products

Close Search

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)
- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)
- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)
- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

Digital

Close Search

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)
- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)
- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)
- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)
- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



MSC motor starters combinations
102967

[Overview](#) [Specifications](#) [Resources](#)

[How to buy](#)

[Back to search](#)

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Previous](#) [Next](#)

[Download](#) [Zoom](#)

- 
- 
- 
- 
- 

[Previous](#) [Next](#)

102967

Eaton Moeller® series MSC-D DOL starter, 380 V 400 V 415 V: 0.25 kW, Ir= 0.63 - 1 A, 24 V DC, DC voltage

[Add a free sample to the cart](#) [How to buy](#)

- [Configurator Motor starter combinations](#)



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

[Keep My Cart](#) [Create a New Cart](#)



Item is already in the cart.

Okay

Photo is representative

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [118561](#)

118561
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC, manual/auto
- [118560](#)

118560
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC
- [101044](#)

101044
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC
- [101043](#)

101043
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC
- [101042](#)

101042
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC
- [101041](#)

101041
Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

Go to Previous Item

Go to Next Item

- [118561](#)

118561
Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MSC, manual/auto
- [118560](#)

118560

Eaton Moeller® series DIL-SWD Function element, contactor, SmartWire-DT, DIL/MS

- [101044](#)

101044

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

- [101043](#)

101043

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

- [101042](#)

101042

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

- [101041](#)

101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

[View more](#) [View less](#)

- General specifications
- Product specifications

General specifications

Product Name
Eaton Moeller® series MSC-D DOL starter
Catalog Number
102967
Model Code
MSC-D-1-M7(24VDC)/BBA
EAN
4015081028061
Product Length/Depth
154 mm
Product Height
200 mm
Product Width
45 mm
Product Weight
0.875 kg
Certifications
CSA-C22.2 No. 14-10
IEC/EN 60947-4-1
UL60947-4-1A
CSA File No.: 012528
CSA-C22.2 No. 14 (on request)
UL 508 (on request)
UL Category Control No.: NKJH
CSA
CSA Class No.: 3211-04
CE
UL File No.: E123500

UL

Product specifications

Rated operational current for specified heat dissipation (In)

1 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated operational power at AC-3, 380/400 V, 50 Hz

0.25 kW

Rated operational voltage

230 - 415 V AC

Rated conditional short-circuit current, type 1, 480 Y/277 V

0 A

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting method

Mounting on Busbar 60 mm

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Rated power at 575 V, 60 Hz, 3-phase

0 kW

Rated power at 460 V, 60 Hz, 3-phase

0 kW

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Rated control supply voltage (Us) at DC - min

24 V

Fitted with:

Short-circuit release

Number of pilot lights

0

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Coordination type

2

10.8 Connections for external conductors

Is the panel builder's responsibility.

Coordination class (IEC 60947-4-3)

Class 2

Rated conditional short-circuit current, type 1, 600 Y/347 V

0 A

Ambient operating temperature - max

55 °C

Rated operational power at AC-3, 220/230 V, 50 Hz

0.12 kW

Connection to SmartWire-DT

No

Number of command positions

0

Static heat dissipation, non-current-dependent Pvs

2.6 W

Electrical connection type of main circuit

Screw connection

Electrical connection type for auxiliary- and control-current circuit

Screw connection

Power consumption (sealing) at DC

3 W

Rated control supply voltage (Us) at DC - max

24 V

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.
Ambient operating temperature - min
-25 °C
10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.
10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.
Class
CLASS 10 A
10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.
10.3 Degree of protection of assemblies
Does not apply, since the entire switchgear needs to be evaluated.
Heat dissipation per pole, current-dependent P_{vid}
1.9 W
Actuating voltage
24 V DC
Voltage type
DC
Switching capacity (auxiliary contacts, general use)
15 A, 600 V AC, (UL/CSA)
1 A, 250 V DC, (UL/CSA)
Overload release current setting - min
0.63 A
Equipment heat dissipation, current-dependent P_{vid}
5.7 W
Heat dissipation capacity P_{diss}
0 W
Rated operational current (I_e)
0.8 A
Suitable for
Also motors with efficiency class IE3
Number of auxiliary contacts (normally closed contacts)
0
Rated conditional short-circuit current (I_q), type 2, 380 V, 400 V, 415 V
50000 A
Power consumption
2.6 W
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects
Meets the product standard's requirements.
Overload release current setting - max
1 A
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.
Overvoltage category
III
Degree of protection
IP20
NEMA Other
Pollution degree
3
Rated control supply voltage (U_s) at AC, 60 Hz - min
0 V
10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.
Rated impulse withstand voltage (U_{imp})
6000 V AC
Connection
Screw terminals

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Functions

Temperature compensated overload protection

Rated conditional short-circuit current (Iq), type 2, 230 V

50000 A

Type

Starter with Bi-Metal release

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Short-circuit release (Irm) - max

15.5 A

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

1 A

Model

Direct starter

Number of auxiliary contacts (normally open contacts)

1

Altitude

Max. 2000 m

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)

P300, DC operated (UL/CSA)

Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Brochures

- [Simple, flexible and safe! Distribution system for motor-starter combinations](#)
- [Save time and space thanks to the new link module PKZM0-XDM32ME](#)
- [Motor Starters in System xStart - brochure](#)

Download all files

Catalogs

- [Product Range Catalog Switching and protecting motors](#)

Declarations of conformity

- [DA-DC-00004878.pdf](#)
- [DA-DC-00004910.pdf](#)

Drawings

- [eaton-manual-motor-starters-adapter-msc-d-dol-starter-dimensions.eps](#)
- [eaton-general-ie-ready-dilm-contactor-standards.eps](#)

Download all files

eCAD model

- [DA-CE-ETN.MSC-D-1-M7\(24VDC\)_BBA](#)

Installation instructions

- [IL034014ZU](#)
- [IL03402015Z](#)
- [IL034038ZU](#)

Download all files

Installation videos

- [WIN-WIN with push-in technology](#)

mCAD model

- [DA-CS-msc_d_bba_bg1](#)
- [DA-CD-msc_d_bba_bg1](#)

Download all files

Wiring diagrams

- [eaton-manual-motor-starters-device-msc-d-dol-starter-wiring-diagram.eps](#)

Export product specification

-



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- ☐ Product pickup
- ☐ Order online and ship product

- 102967

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-

-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

Back to top of the page

Are you sure?

Cancel Sign out

Are you sure?

Cancel Sign out

×

×