

[United States](#) [Select your location](#)

Search parts, catalogs

[Sign in](#)

We make what matters work*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

[Search](#) [Toggle Mobile Menu](#)

Search

Search



[Products](#)

[Close Search](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)
- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)
- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)
- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

[Close Search](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

[Close Search](#)

[Markets](#)

[Close Search](#)

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)
- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)
- [Vehicles](#)

[Support](#)

[Close Search](#)

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

[Close Search](#)

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)
- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)
- [Selling to Eaton](#)

[MyEaton](#)

[Close Search](#)

[Quick links](#)



MSC motor starters combinations
102991

[Overview](#) [Specifications](#) [Resources](#)

[How to buy](#)

[Back to search](#)

[Download](#) [Zoom](#)


[Download](#) [Zoom](#)

[Download](#) [Zoom](#)

[Download](#) [Zoom](#)

[Previous](#) [Next](#)

[Download](#) [Zoom](#)



[Previous](#) [Next](#)

102991

Eaton Moeller® series MSC-R Reversing starter, 380 V 400 V 415 V: 5.5 kW, Ir= 8 - 12 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage MSC-R-12-M12(230V50HZ)/BBA

[Add a free sample to the cart](#) [How to buy](#)

- [Configurator Motor starter combinations](#)



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

[Keep My Cart](#) [Create a New Cart](#)



Item is already in the cart.

[Okay](#)

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [101044](#)

101044

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

- [101043](#)

101043

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

- [101042](#)

101042

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

- [101041](#)

101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

[Go to Previous Item](#) [Go to Next Item](#)

- [101044](#)

101044

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

- [101043](#)

101043

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

- [101042](#)

101042

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

- [101041](#)

101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

[View more](#) [View less](#)

- [General specifications](#)
- [Product specifications](#)

General specifications

Product Name
Eaton Moeller® series MSC-R Reversing starter
Catalog Number
102991
Model Code
MSC-R-12-M12(230V50HZ)/BBA
EAN
4015081028306
Product Length/Depth
200 mm
Product Height
153 mm
Product Width
90 mm
Product Weight
1.56 kg
Certifications
UL Category Control No.: NKJH
UL
UL 508 (on request)
UL60947-4-1A
CSA
CSA-C22.2 No. 14-10
CSA-C22.2 No. 14 (on request)
UL File No.: E123500
CE
IEC/EN 60947-4-1
CSA Class No.: 3211-04
CSA File No.: 012528

Product specifications

Rated operational current for specified heat dissipation (In)
12 A
10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
Rated operational power at AC-3, 380/400 V, 50 Hz
5.5 kW
Rated operational voltage
230 - 415 VAC
Rated conditional short-circuit current, type 1, 480 Y/277 V
0 A
Rated control supply voltage (Us) at AC, 50 Hz - min
230 V
10.4 Clearances and creepage distances
Meets the product standard's requirements.
10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
Mounting method
Rail mounting possible
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.
Rated power at 575 V, 60 Hz, 3-phase
0 kW
Rated power at 460 V, 60 Hz, 3-phase
0 kW
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.
Rated control supply voltage (Us) at DC - min
0 V
Fitted with:
Short-circuit release
Number of pilot lights

0
Rated control supply voltage (Us) at AC, 50 Hz - max

230 V

Coordination type

1

10.8 Connections for external conductors

Is the panel builder's responsibility.

Coordination class (IEC 60947-4-3)

Class 1

Rated conditional short-circuit current, type 1, 600 Y/347 V

0 A

Power consumption, sealing, 50 Hz

1.2 W, Dual-frequency coil in a cold state and $1.0 \times Us$, at 50 Hz

Ambient operating temperature - max

55 °C

Rated operational power at AC-3, 220/230 V, 50 Hz

3 kW

Connection to SmartWire-DT

No

Number of command positions

0

Static heat dissipation, non-current-dependent Pvs

1.4 W

Electrical connection type of main circuit

Screw connection

Electrical connection type for auxiliary- and control-current circuit

Screw connection

Rated control supply voltage (Us) at DC - max

0 V

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Class

CLASS 10 A

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent Pvid

3.1 W

Actuating voltage

230 V 50 Hz

240 V 60 Hz

Voltage type

AC

Switching capacity (auxiliary contacts, general use)

1 A, 250 VDC, (UL/CSA)

15 A, 600 VAC, (UL/CSA)

Overload release current setting - min

8 A

Equipment heat dissipation, current-dependent Pvid

9.3 W

Heat dissipation capacity Pdiss

0 W

Rated operational current (Ie)

11.3 A

Suitable for
Also motors with efficiency class IE3
Number of auxiliary contacts (normally closed contacts)
0
Rated conditional short-circuit current (Iq), type 2, 380 V, 400 V, 415 V
100 A
Power consumption
1.4 W
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects
Meets the product standard's requirements.
Overload release current setting - max
12 A
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.
Overvoltage category
III
Degree of protection
IP20
NEMA Other
Pollution degree
3
Rated control supply voltage (Us) at AC, 60 Hz - min
0 V
10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.
Rated impulse withstand voltage (Uimp)
6000 VAC
Connection
Screw terminals
10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
Functions
Temperature compensated overload protection
Rated conditional short-circuit current (Iq), type 2, 230 V
0 A
Type
Starter with Bi-Metal release
10.2.2 Corrosion resistance
Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.
10.2.7 Inscriptions
Meets the product standard's requirements.
Short-circuit release (Irm) - max
186 A
Rated control supply voltage (Us) at AC, 60 Hz - max
0 V
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V
12 A
Model
Reversing starter
Number of auxiliary contacts (normally open contacts)
0
Altitude
Max. 2000 m
Switching capacity (auxiliary contacts, pilot duty)
A600, AC operated (UL/CSA)
P300, DC operated (UL/CSA)
Serial Number Verified :
Authenticated: ✓
The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

- [Save time and space thanks to the new link module PKZM0-XDM32ME](#)
- [Simple, flexible and safe! Distribution system for motor-starter combinations](#)
- [Motor Starters in System xStart - brochure](#)

[Download all files](#)

Catalogs

- [Product Range Catalog Switching and protecting motors](#)

Declarations of conformity

- [DA-DC-00004878.pdf](#)
- [DA-DC-00004910.pdf](#)

Drawings

- [eaton-manual-motor-starters-busbar-msc-r-reversing-starter-dimensions-002.eps](#)
- [eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[Download all files](#)

eCAD model

- [DA-CE-ETN.MSC-R-12-M12\(230V50HZ\)_BBA](#)

Installation instructions

- [IL03402006Z](#)
- [IL03402015Z](#)

[Download all files](#)

Installation videos

- [WIN-WIN with push-in technology](#)

mCAD model

- [DA-CS-msc_r_bba_bg1](#)
- [DA-CD-msc_r_bba_bg1](#)

[Download all files](#)

Wiring diagrams

- [eaton-manual-motor-starters-starter-msc-r-reversing-starter-wiring-diagram.eps](#)

[Export product specification](#)

•



Locate me

Enter your city, state, or zip code or

City, state

Search

Show locations that offer:

Product pickup

Order online and ship product

- 102991

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

[Back to top of the page](#)

Are you sure?

Are you sure?