



MSC MOTOR STARTERS COMBINATIONS
102992



Overview



Specifications



Resources

How to

102992


Eaton Moeller® series MSC-R Reversing starter, 380 V, 6.3 - 10 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage




How to buy



Configurator Motor starter combinations





GENERAL SPECIFICATIONS

General specifications

**PRODUCT NAME**

Eaton Moeller® series MSC-R Reversing starter

Product specifications

**CATALOG NUMBER**

102992

MODEL CODE

MSC-R-10-M17(230V50HZ)/BBA

EAN

4015081028313

PRODUCT LENGTH/DEPTH

200 mm

PRODUCT HEIGHT

157 mm

PRODUCT WIDTH

90 mm

PRODUCT WEIGHT

1.73 kg

CSA File No.: 012528
CSA-C22.2 No. 14-10

CERTIFICATIONS

UL 508 (on request)
UL60947-4-1A
CSA Class No.: 3211-04
UL
UL Category Control No.: NKJH
IEC/EN 60947-4-1
UL File No.: E123500
CSA
CE
CSA-C22.2 No. 14 (on request)

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 10 A

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specification must be observed.

RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ 4 kW

RATED OPERATIONAL VOLTAGE

230 - 415 V AC

RATED CONDITIONAL SHORT-CIRCUIT CURRENT, TYPE 1, 480 Y/277 V 0 A

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN 230 V

10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specification must be observed.

MOUNTING METHOD

DIN rail

10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be lifted.

RATED POWER AT 575 V, 60 HZ, 3-PHASE

0 kW

RATED POWER AT 460 V, 60 HZ, 3-PHASE

0 kW

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN 0 V

FITTED WITH:

Short-circuit release

NUMBER OF PILOT LIGHTS

0

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX 230 V

COORDINATION TYPE

2

10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS

Is the panel builder's responsibility.

COORDINATION CLASS (IEC 60947-4-3)

Class 2

RATED CONDITIONAL SHORT-CIRCUIT CURRENT, TYPE 1, 600 Y/347 V	0 A
POWER CONSUMPTION, SEALING, 50 Hz	2.1 W, Dual-frequency coil in a cold state and 1.0 x
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
RATED OPERATIONAL POWER AT AC-3, 220/230 V, 50 Hz	2.2 kW
CONNECTION TO SMARTWIRE-DT	No
NUMBER OF COMMAND POSITIONS	0
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	2.1 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
ELECTRICAL CONNECTION TYPE FOR AUXILIARY- AND CONTROL-CURRENT CIRCUIT	Screw connection
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
CLASS	CLASS 10 A
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	2.7 W
ACTUATING VOLTAGE	230 V 50 Hz 240 V 60 Hz
VOLTAGE TYPE	AC
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	15 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
OVERLOAD RELEASE CURRENT SETTING - MIN	6.3 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	8.1 W
HEAT DISSIPATION CAPACITY PDISS	0 W

RATED OPERATIONAL CURRENT (IE)	8.5 A
SUITABLE FOR	Also motors with efficiency class IE3
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ), TYPE 2, 380 V, 400 V, 415 V	50000 A
POWER CONSUMPTION	2.1 W
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
OVERLOAD RELEASE CURRENT SETTING - MAX	10 A
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	IP00 NEMA Other
POLLUTION DEGREE	3
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	0 V
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
CONNECTION	Screw terminals
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
FUNCTIONS	Temperature compensated overload protection
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ), TYPE 2, 230 V	50000 A
TYPE	Starter with Bi-Metal release
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHORT-CIRCUIT RELEASE (IRM) - MAX	155 A
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	0 V
RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 10 A	10 A

MODEL	Reversing starter
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
ALTITUDE	Max. 2000 m
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)

Brochures

Catalogs

Declarations of conformity

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

Wiring diagrams

102992



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By

capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.