

[United States](#) [Select your location](#)

Search parts, catalogs

[Sign in](#)

We make what matters work\*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

[Search](#) [Toggle Mobile Menu](#)

Search

Search



[Products](#)

[Close Search](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)
- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)
- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)
- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

[Close Search](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

## [Services](#)

[Close Search](#)

## [Markets](#)

[Close Search](#)

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)
- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)
- [Vehicles](#)

## [Support](#)

[Close Search](#)

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

## [Company](#)

[Close Search](#)

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)
- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)
- [Selling to Eaton](#)

## [MyEaton](#)

[Close Search](#)

## [Quick links](#)



MSC motor starters combinations  
103005

[How to buy](#)

[Back to search](#)

[Download](#) [Zoom](#)

[Download](#) [Zoom](#)

## 103005

Eaton Moeller® series MSC-R Reversing starter, 380 V 400 V 415 V: 3 kW, Ir= 6.3 - 10 A, 24 VDC, DC voltage MSC-R-10-M7(24VDC)/BBA

[Add a free sample to the cart](#) [How to buy](#)

- [Configurator Motor starter combinations](#)



### Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

[Keep My Cart](#) [Create a New Cart](#)



### Item is already in the cart.

[Okay](#)

### Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [101044](#)

101044

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

- [101043](#)

101043

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

- [101042](#)

101042

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

- [101041](#)

101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

[Go to Previous Item](#)

[Go to Next Item](#)

- [101044](#)

101044

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

- [101043](#)

101043

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

- [101042](#)

101042

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, MSC

- [101041](#)

101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

[View more](#) [View less](#)

- [General specifications](#)
- [Product specifications](#)

## General specifications

Product Name

Eaton Moeller® series MSC-R Reversing starter

Catalog Number

103005

Model Code

MSC-R-10-M7(24VDC)/BBA

EAN

4015081028443

Product Length/Depth

200 mm

Product Height

153 mm

Product Width

90 mm

Product Weight

1.67 kg

Certifications

CSA File No.: 012528

UL 508 (on request)

CSA

CSA-C22.2 No. 14 (on request)

IEC/EN 60947-4-1

UL Category Control No.: NKJH

UL

UL File No.: E123500

CE

CSA-C22.2 No. 14-10

UL60947-4-1A

CSA Class No.: 3211-04

## Product specifications

Rated operational current for specified heat dissipation (In)

10 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated operational power at AC-3, 380/400 V, 50 Hz

3 kW

Rated operational voltage

230 - 415 VAC

Rated conditional short-circuit current, type 1, 480 Y/277 V

0 A

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting method

Rail mounting possible

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Rated power at 575 V, 60 Hz, 3-phase

0 kW

Rated power at 460 V, 60 Hz, 3-phase

0 kW

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Rated control supply voltage (Us) at DC - min

24 V

Fitted with:

Short-circuit release

Number of pilot lights

0

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Coordination type

1

10.8 Connections for external conductors

Is the panel builder's responsibility.

Coordination class (IEC 60947-4-3)

Class 1

Rated conditional short-circuit current, type 1, 600 Y/347 V

0 A

Ambient operating temperature - max

55 °C

Rated operational power at AC-3, 220/230 V, 50 Hz

1.5 kW

Connection to SmartWire-DT

No

Number of command positions

0

Static heat dissipation, non-current-dependent Pvs

2.6 W

Electrical connection type of main circuit

Screw connection

Electrical connection type for auxiliary- and control-current circuit

Screw connection  
Power consumption (sealing) at DC

3 W  
Rated control supply voltage (Us) at DC - max  
24 V

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Class

CLASS 10 A

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent Pvid

3.1 W

Actuating voltage

24 VDC

Voltage type

DC

Switching capacity (auxiliary contacts, general use)

1 A, 250 VDC, (UL/CSA)

15 A, 600 VAC, (UL/CSA)

Overload release current setting - min

6.3 A

Equipment heat dissipation, current-dependent Pvid

9.3 W

Heat dissipation capacity Pdiss

0 W

Rated operational current (Ie)

6.6 A

Suitable for

Also motors with efficiency class IE3

Number of auxiliary contacts (normally closed contacts)

0

Rated conditional short-circuit current (Iq), type 2, 380 V, 400 V, 415 V

100 A

Power consumption

2.6 W

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Overload release current setting - max

10 A

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Overvoltage category

III

Degree of protection

IP20

NEMA Other

Pollution degree

3

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

## 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Rated impulse withstand voltage (U<sub>imp</sub>)

6000 V AC

Connection

Screw terminals

## 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Functions

Temperature compensated overload protection

Rated conditional short-circuit current (I<sub>q</sub>), type 2, 230 V

0 A

Type

Starter with Bi-Metal release

## 10.2.2 Corrosion resistance

Meets the product standard's requirements.

## 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

## 10.2.7 Inscriptions

Meets the product standard's requirements.

Short-circuit release (I<sub>rm</sub>) - max

155 A

Rated control supply voltage (U<sub>s</sub>) at AC, 60 Hz - max

0 V

Rated operational current (I<sub>e</sub>) at AC-3, 380 V, 400 V, 415 V

7 A

Model

Reversing starter

Number of auxiliary contacts (normally open contacts)

0

Altitude

Max. 2000 m

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)

P300, DC operated (UL/CSA)

Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

## Brochures

- [Simple, flexible and safe! Distribution system for motor-starter combinations](#)
- [Save time and space thanks to the new link module PKZM0-XDM32ME](#)
- [Motor Starters in System xStart - brochure](#)

[Download all files](#)

## Catalogs

- [Product Range Catalog Switching and protecting motors](#)

## Declarations of conformity

- [DA-DC-00004878.pdf](#)
- [DA-DC-00004910.pdf](#)

## Drawings

- [eaton-manual-motor-starters-busbar-msc-r-reversing-starter-dimensions-002.eps](#)
- [eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[Download all files](#)

## eCAD model

- [DA-CE-ETN.MSC-R-10-M7\(24VDC\)\\_BBA](#)

## Installation instructions

- [IL03402015Z](#)
- [IL03402006Z](#)

[Download all files](#)

## Installation videos

- [WIN-WIN with push-in technology](#)

## mCAD model

- [DA-CD-msc\\_r\\_bba\\_bg1](#)
- [DA-CS-msc\\_r\\_bba\\_bg1](#)

[Download all files](#)

## Wiring diagrams

- [eaton-manual-motor-starters-starter-msc-r-reversing-starter-wiring-diagram.eps](#)

## Export product specification

•



Locate me

Enter your city, state, or zip code or

City, state

[Search](#)

Show locations that offer:

Product pickup  
 Order online and ship product

- 103005

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)

- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

- 
- 
- 
- 

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

[Back to top of the page](#)

Are you sure?

[Cancel](#) [Sign out](#)

Are you sure?

[Cancel](#) [Sign out](#)



