




PKE ELECTRONIC MOTOR PROTECTION
CIRCUIT BREAKER
138261


Overview


Specifications


Resources

How to buy



138261

Eaton Moeller® series PKE Trip block, 8 - 32 A, Moeller®
to SmartWire-DT: no, For use with: PKE65 basic de

How to buy





GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME Eaton Moeller® series PKE Trip block

CATALOG NUMBER 138261

Product specifications



MODEL CODE PKE-XTUW-32

EAN 4015081350414

PRODUCT LENGTH/DEPTH 84.4 mm

PRODUCT HEIGHT 69.9 mm

PRODUCT WIDTH 55 mm

PRODUCT WEIGHT 0.196 kg

CSA-C22.2 No. 14-10
VDE 0660

CERTIFICATIONS

UL
CSA File No.: 165628
CE
IEC/EN 60947
IEC/EN 60947-4-1
CSA Class No.: 3211-05
CSA
UL 508
UL File No.: E36332
UL Category Control No.: NLRV

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	32 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	0 V
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
CUT-OUT PERIODS - MIN	≤ 500 ms, main conducting paths, AC-4 cycle operation
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
CURRENT FLOW TIMES - MIN	500 (Class 5) AC-4 cycle operation, Main conducting paths 700 (Class 10) AC-4 cycle operation, Main conducting paths 1000 (Class 20) AC-4 cycle operation, Main conducting paths Note: Going below the minimum current flow time of the load (motor). 900 (Class 15) AC-4 cycle operation, Main conducting paths For all combinations with an SWD activation, you must observe the minimum current flow times and minimum cut-off times
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	0 V
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
PROTECTION	Finger and back-of-hand proof, Protection against direct contact, Protection against contact when actuated from front (EN 50274)

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-2 Part 102)
CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
RATED CONTROL SUPPLY VOLTAGE(US) AT DC - MAX	0 V
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
NUMBER OF POLES	Three-pole
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be tested.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be tested.
RATED UNINTERRUPTED CURRENT (IU)	32 A
SHORT-CIRCUIT RELEASE	± 20% tolerance, Trip blocks Trip block fixed 15.5 x Ir Delayed approx. 60 ms, Trip blocks
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instructions in the instruction leaflet (IL) is observed.
SWITCHING CAPACITY AT AC-3 (UP TO 690 V)	32 A
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be tested.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be tested.
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.3 W
OPERATING FREQUENCY	60 Operations/h
VOLTAGE TYPE	Self-powered
SHORT-CIRCUIT RELEASE FUNCTION	Delayed
PRODUCT CATEGORY	Accessories
OVERLOAD RELEASE CURRENT SETTING - MIN	8 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	3.9 W
HEAT DISSIPATION CAPACITY PDISS	0 W

RATED OPERATIONAL CURRENT (IE)	32 A
TEMPERATURE COMPENSATION	-25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660
RATED FREQUENCY - MIN	50 Hz
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
OVERLOAD RELEASE CURRENT SETTING - MAX	32 A
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	Device: IP20 Terminals: IP00
OVERVOLTAGE CATEGORY	III
RATED FREQUENCY - MAX	60 Hz
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
UNDELAYED SHORT-CIRCUIT RELEASE - MIN	96 A
POLLUTION DEGREE	3
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	0 V
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device
FUNCTIONS	Motor protection Overload release Motor protection for heavy starting duty
PROTECTION TYPE	Electronic release
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	0 V
UNDELAYED SHORT-CIRCUIT RELEASE - MAX	384 A
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27 shock 10 ms

Brochures

Catalogs

Certification reports

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Installation videos

Manuals and user guides

mCAD model

138261



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to

solve the world’s most urgent power management challenges.