




RMQ TITAN MODULAR PILOT DEVICES
110918


Overview


Specifications


Resources

How to



110918

Eaton Moeller® series M22 Key-operated actuator, 2 positions, 2 NO

Contact me about this product



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10

216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

216384

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A

216380

Eaton Moeller® series M22 Contact element, Screw terminals, Base fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-KC10

View more

View less

General specifications

>

PRODUCT NAME	Eaton Moeller® series M22 Key-operated actuator
CATALOG NUMBER	110918
MODEL CODE	M22-WRS-2K10-BVP
EAN	4015081104475
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	50 mm
PRODUCT WEIGHT	0.063 kg
COMPLIANCES	CE
CERTIFICATIONS	DNV GL LR

Product specifications

>

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
PRODUCT CATEGORY	RMQ-Titan
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
OPENING DIAMETER	22.5 mm
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FITTED WITH:	Front ring
WIDTH OPENING	0 mm
DEGREE OF PROTECTION (FRONT SIDE)	IP66
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL	Meets the product standard's requirements.

HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
BEZEL MATERIAL	Plastic
NUMBER OF SWITCH POSITIONS	2
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
ACTUATOR TYPE	Key
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	NEMA 4X
ACTUATOR COLOR	Black
OPENING HEIGHT	0 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
POLLUTION DEGREE	3
BEZEL COLOR	Titanium
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
INDICATOR COLOR	Other
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature. Eaton will provide heat dissipation data for the device.
CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
LENS TYPE	Round
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be specified.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be specified.
ACTUATOR FUNCTION	Switching function latching
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the installation instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be specified.

10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.11 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

mCAD model

System overview

110918



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.

