




RMQ TITAN MODULAR PILOT DEVICES
110934


Overview


Specifications


Resources


How to



110934

Eaton Moeller® series M22 Pushbutton, RMQ-Titan
green, Blister pack for hanging

Contact me about this product



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216395

Eaton Moeller® series M22 Key-protection diaphragm, for pushbutton + indicator light

231274

Eaton Moeller® series M22 Guard-ring, selector switch

View more

View less

GENERAL SPECIFICATIONS

General specifications	>	PRODUCTNAME	Eaton Moeller® series M22 Pushbutton
		CATALOG NUMBER	110934
Product specifications	>	MODEL CODE	M22-D-G-K10-BVP
		EAN	4015081104635
		PRODUCT LENGTH/DEPTH	50 mm
		PRODUCT HEIGHT	80 mm
		PRODUCT WIDTH	50 mm
		PRODUCT WEIGHT	0.025 kg
		COMPLIANCES	CE
		CERTIFICATIONS	DNV GL LR

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
PRODUCT CATEGORY	RMQ-Titan
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
OPENING DIAMETER	22 mm
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W

HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FRONT ELEMENT TYPE	Flat
FITTED WITH:	Front ring
DEGREE OF PROTECTION (FRONT SIDE)	NEMA 4X IP67
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
BEZEL MATERIAL	Plastic
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
ACTUATOR COLOR	Green
OPENING HEIGHT	0 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Chrome
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
CONNECTION TO SMARTWIRE-DT	No
NUMBER OF COMMAND POSITIONS	1
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
LENS TYPE	Round
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND	

COMPONENTS	Does not apply, since the entire switchgear needs to
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
ACTUATOR FUNCTION	Spring-return
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.11 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

mCAD model

System overview



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.