



DIL CONTACTORS
281218



Overview



Specifications





Resources

How to

281218

Eaton Moeller® series DILM Varistor suppressor c
use with: DILM40 - DILM95, DILK33 - DILK50, DIL
DILM95-XSPV240



-  WIN-WIN with Push-in Terminals
-  How to improve wiring




Photo is representative




Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.



294044

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 33.3 kVAr, 48 V 50 Hz



294074

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 50 kVAr, 190 V 50 Hz, 220 V 60 Hz



294066

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 50 kVAr, 48 V 50 Hz



294056

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 50 kVAr, 400 V 50 Hz, 440 V 60 Hz

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME	Eaton Moeller® series DILM varistor suppressor circuit
--------------	--

CATALOG NUMBER	281218
----------------	--------

Product specifications

>

MODEL CODE	DILM95-XSPV240
------------	----------------

EAN	4015082812188
-----	---------------

PRODUCT LENGTH/DEPTH	43 mm
----------------------	-------

PRODUCT HEIGHT	25 mm
----------------	-------

PRODUCT WIDTH	9 mm
---------------	------

PRODUCT WEIGHT	0.005 kg
----------------	----------

CERTIFICATIONS

CE
UL 508
CSA-C22.2 No. 14-05
CSA
UL Recognized
CSA File No.: 256465
UL File No.: E29184
UL Category Control No.: NKCR2, NKCR8
CSA Class No.: 3211-07
IEC/EN 60947-4-1

CATALOG NOTES

With DC operated contactors and with DILM115 arcing suppressor is integrated.

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	Accessories
------------------	-------------

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
---	-----

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
----------------------------	--

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
--	-----

HEAT DISSIPATION CAPACITY PDISS	0 W
---------------------------------	-----

OPERATING VOLTAGE AT AC, 50 HZ - MAX	690 V
--------------------------------------	-------

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	130 V
--	-------

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
--	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
OPERATING VOLTAGE AT DC - MAX	0 V
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
OPERATING VOLTAGE AT AC, 60 HZ - MAX	690 V
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
OPERATING VOLTAGE AT DC - MIN	0 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
VOLTAGE TYPE OF OPERATING VOLTAGE	AC
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	130 V
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise. Eaton will provide heat dissipation data for the device.
FUNCTIONS	Varistor (voltage-sensitive resistor)
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
OPERATING VOLTAGE AT AC, 60 HZ - MIN	230 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be tested.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
OPERATING VOLTAGE AT AC, 50 HZ - MIN	230 V
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
VOLTAGE TYPE	AC

Catalogs

Certification reports

Declarations of conformity

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

Wiring diagrams



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.