





**BIMETAL OVERLOAD RELAYS**  
**215218**

  
Overview

  
Specifications

  
Resources

How to



215218

Eaton Moeller® series Z5 Terminal shroud, for Z5/1

How to buy





## Designed to work together

Discover other Eaton products and accessories built to enhance this product.



### 210075

Eaton Moeller® series Z5 Overload relay,  
I<sub>r</sub>= 200 - 250 A, 1 N/O, 1 N/C, For use  
with: DILM250, DILM300A




### 139573

Eaton Moeller® series Z5 Overload relay,  
I<sub>r</sub>= 70 - 100 A, 1 N/O, 1 N/C, For use with:  
DILM185A, DILM225A



### 139578

Eaton Moeller® series Z5 Overload relay,  
I<sub>r</sub>= 200 - 300 A, 1 N/O, 1 N/C, For use  
with: DILM300A



### 139577

Eaton Moeller® series Z5 Overload relay,  
I<sub>r</sub>= 200 - 250 A, 1 N/O, 1 N/C,  
with: DILM185A, DILM225A

View more

View less

## GENERAL SPECIFICATIONS

General specifications	>	PRODUCT NAME	Eaton Moeller® series Z5 Accessory Terminal cover
		CATALOG NUMBER	215218
Product specifications	>	MODEL CODE	Z5/FF250-XHB-Z
		EAN	4015082152185
		PRODUCT LENGTH/DEPTH	77 mm
		PRODUCT HEIGHT	61 mm
		PRODUCT WIDTH	150 mm
		PRODUCT WEIGHT	0.09 kg
		COMPLIANCES	CE

## PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	Accessories
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
ACCESSORY/SPARE PART TYPE	Shock protection cover
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MAX	60 °C

<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be tested.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be tested.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the instruction leaflet (IL) is observed.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be tested.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be tested.
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W

Catalogs

Declarations of conformity

Drawings

eCAD model

Installation instructions

Manuals and user guides

215218



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.