



## ZEB MOTOR PROTECTION RELAYS

136492



Overview




Specifications



Resources

How to buy



136492

Eaton Moeller® series ZEB Overload relay, Direct trip protection: with, Ir= 4 - 20 A, 1 N/O, 1 N/C ZEB32-2

How to buy



Photo is representative

## Designed to work together

Discover other Eaton products and accessories built to enhance this product.

100421

Eaton Moeller® series SDAINL Star-delta contactor combination, 380 V 400 V: 30 kW, 24 V DC, DC operation

100420

Eaton Moeller® series SDAINL Star-delta contactor combination, 380 V 400 V: 22 kW, 24 V DC, DC operation

100419

Eaton Moeller® series SDAINL Star-delta contactor combination, 380 V 400 V: 15 kW, 24 V DC, DC operation

278386

Eaton Moeller® series SDAINL contactor combination, 380 V 400 kW, 230 V 50 Hz, 240 V 60 Hz operation

[View more](#)

[View less](#)

## GENERAL SPECIFICATIONS

General specifications

>

### PRODUCT NAME

Eaton Moeller® series ZEB Electronic overload Rel

Product specifications

>

### CATALOG NUMBER

136492

### MODEL CODE

ZEB32-20-GF

### EAN

4015081332724

### PRODUCT LENGTH/DEPTH

108 mm

### PRODUCT HEIGHT

110 mm

### PRODUCT WIDTH

45 mm

### PRODUCT WEIGHT

0.271 kg

### CERTIFICATIONS

CSA

UL

UL 508

IEC/EN 60947-4-1

CSA File No.: 2290956

CSA-C22.2 No. 14

UL Category Control No.: NKCR

CSA Class No.: 3211-03

VDE 0660

CE

IEC/EN 60947

UL File No.: E1230

### CATALOG NOTES

Rated operational current: Switch-on and switch-off DC-13, time constant as specified.

## PRODUCT SPECIFICATIONS

### RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)

20 A

### TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)

2 x (0.75 - 2.5) mm<sup>2</sup>, Control circuit cables

### 10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specification must be observed.

### STRIPPING LENGTH (CONTROL CIRCUIT CABLE)

8 mm

### OPERATING VOLTAGE AT AC, 50 HZ - MAX

690 V

### RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN

0 V

### 10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

### 10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specification must be observed.

### MOUNTING METHOD

Direct mounting  
Direct attachment

### 10.2.5 LIFTING

Does not apply since the entire switchgear needs to

<b>STRIPPING LENGTH (MAIN CABLE)</b>	13 mm
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	65 °C
<b>OPERATING VOLTAGE AT DC - MAX</b>	0 V
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>RESET FUNCTION</b>	Push-button Automatic
<b>RATED CONTROL SUPPLY VOLTAGE (US) ATDC - MIN</b>	0 V
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)</b>	100 kA, Fuse, SCCR (UL/CSA) 60 A, Class J, max. Fuse, SCCR (UL/CSA)
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	0 V
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>SCREW SIZE</b>	M3.5, Terminal screw, Control circuit cables
<b>ADJUSTABLE CURRENT RANGE - MIN</b>	4 A
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct actuated from front (EN 50274)
<b>OPERATING VOLTAGE AT DC - MIN</b>	0 V
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	65 °C
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>FEATURES</b>	Phase-failure sensitivity (according to IEC/EN 60940-102)
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>RATED CONTROL SUPPLY VOLTAGE (US) ATDC - MAX</b>	0 V
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>VOLTAGE RATING - MAX</b>	600 V
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to
<b>EARTH FAULT PROTECTION</b>	Yes Trip at approx. > 1.5 x Ir in 1 s Trip at approx. > 0.5 x Ir in 2 s

**SAFE ISOLATION**

240 V AC, Between auxiliary contacts, According to EN 61140  
440 V, Between auxiliary contacts and main contact  
61140  
600 V AC, Between main circuits, According to EN 61140

**OPERATING VOLTAGE AT AC, 50 HZ - MIN**

230 V

**RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V**

1.5 A

**CLASS**

Adjustable

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the instruction leaflet (IL) is observed.

**10.2.6 MECHANICAL IMPACT**

Does not apply, since the entire switchgear needs to

**10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL**

Is the panel builder's responsibility.

**NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)**

1

**10.3 DEGREE OF PROTECTION OF ASSEMBLIES**

Does not apply, since the entire switchgear needs to

**HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID**

0.77 W

**RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V**

0.9 A

**VOLTAGE TYPE**

Self powered

**PRODUCT CATEGORY**

Electronic overload relays ZEB

**OVERLOAD RELEASE CURRENT SETTING - MIN**

4 A

**EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID**

2.3 W

**HEAT DISSIPATION CAPACITY PDISS**

0 W

**RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V**

0.75 A

**SUITABLE FOR**

Branch circuits, (UL/CSA)

**TERMINAL CAPACITY (SOLID)**

1 x (1.5 - 16) mm<sup>2</sup>, Main cables  
2 x (0.75 - 4) mm<sup>2</sup>, Control circuit cables

**NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)**

1

**RATED FREQUENCY - MIN**

50 Hz

**10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT**

Meets the product standard's requirements.

**10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS**

Meets the product standard's requirements.

**RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V**

0.2 A

<b>CONVENTIONAL THERMAL CURRENT RATING OF AUXILIARY CONTACTS (1-POLE, OPEN)</b>	5 A
<b>OPERATING VOLTAGE AT AC, 60 HZ - MAX</b>	690 V
<b>OVERLOAD RELEASE CURRENT SETTING - MAX</b>	20 A
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	1 x (14 - 4), Main cables 2 x (18 - 12), Control circuit cables
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>DEGREE OF PROTECTION</b>	IP20
<b>OVERVOLTAGE CATEGORY</b>	III
<b>RATED FREQUENCY - MAX</b>	60 Hz
<b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>VOLTAGE TYPE OF OPERATING VOLTAGE</b>	AC
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	690 V
<b>POLLUTION DEGREE</b>	3
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	0 V
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V (auxiliary circuits) 6000 V AC
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
<b>FUNCTIONS</b>	Filament bulb (24 V)
<b>OPERATING VOLTAGE AT AC, 60 HZ - MIN</b>	230 V
<b>TIGHTENING TORQUE</b>	7 lb-in, Screw terminals 0.8 - 1.2 Nm, Screw terminals, Control circuit cable
<b>ADJUSTABLE CURRENT RANGE - MAX</b>	20 A
<b>SCREWDRIVER SIZE</b>	1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V</b>	1.5 A
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	0 V
<b>NUMBER OF CONTACTS (NORMALLY OPEN</b>	1

**CONTACTS)****SHORT-CIRCUIT PROTECTION RATING**

Max. 6 A gG/gL, fuse, Without welding, Auxiliary

**NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)**

1

**RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V**

0.4 A

**SHOCK RESISTANCE**15 g, Mechanical, According to IEC/EN 60068-2-27  
ms

Mechanical, According to IEC/EN 60068-2-27

**RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V**

0.9 A

**SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)**R300, DC operated (UL/CSA)  
B600, AC operated (UL/CSA)

---

**Brochures**

---

**Characteristic curve**

---

**Declarations of conformity**

---

**Drawings**

---

**eCAD model**

---

**Installation instructions**

---

**mCAD model**

---

**Wiring diagrams**

136492



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are

guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.