




ZEB MOTOR PROTECTION RELAYS
136515


Overview


Specifications


Resources


How to buy



136515

Eaton Moeller® series ZEB Reset extension, for ZEB

How to buy



GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME Eaton Moeller® series ZEB Reset bar

CATALOG NUMBER 136515

Product specifications



MODEL CODE ZEB-XRB

EAN 4015081332953

PRODUCT LENGTH/DEPTH 25 mm

PRODUCT HEIGHT 12 mm

PRODUCT WIDTH 45 mm

PRODUCT WEIGHT 0.014 kg

CERTIFICATIONS

IEC/EN 60947-4-1
UL 508
CSA-C22.2 No. 14
CE

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	Accessories
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
ACCESSORY/SPARE PART TYPE	Other
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP20
AMBIENT OPERATING TEMPERATURE - MAX	65 °C
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
FUNCTIONS	Enlargement of reset
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
VOLTAGE RATING - MAX	600 V
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be tested.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be tested.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be tested.
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

Brochures

Drawings

eCAD model

Installation instructions

mCAD model

136515



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.

