



SL4/SL7 SIGNAL TOWERS
171323


Overview


Specifications


Resources

Contact



171323

Eaton Moeller® series SL4 Continuous light modul

How to buy

Photo is representative



Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

171297

Eaton Moeller® series SL4 Base module;100-mm aluminum tube and foot

171303

Eaton Moeller® series SL4 Base module;for vertical mounting on one sides

171302

Eaton Moeller® series SL4 Base module;external fixing holes

171305

Eaton Moeller® series SL4 Base module;100 mm aluminum tube

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME

Eaton Moeller® series SL4 Continuous light modu

CATALOG NUMBER

171323

Product specifications

>

MODEL CODE

SL4-L120-Y

EAN

4015081678624

PRODUCT LENGTH/DEPTH

43 mm

PRODUCT HEIGHT

75 mm

PRODUCT WIDTH

43 mm

PRODUCT WEIGHT

0.043 kg

CERTIFICATIONS

Certified by UL for use in Canada
IEC/EN 60947-5-1
CE
IEC/EN 60529
UL
UL 508
CSA-C22.2 No. 94-91
UL report applies to both US and Canada
CSA Class No.: NKCR7
UL File No.: E29184
UL Category Control No.: NKCR
CSA-C22.2 No. 14-10

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY

SL signal towers

ENCLOSURE COLOR

Black

RADIATION ANGLE

360 °

LEAKAGE CURRENT

0.003 A

OUTSIDE DIAMETER

43 mm

LIGHT MODULES

LED

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN

110 V

LIGHT TYPE

Continuous light

DEGREE OF PROTECTION

NEMA 4X
IP66

OVERVOLTAGE CATEGORY

III

RATED OPERATIONAL VOLTAGE(UE) AT DC - MIN	0 V
RATED OPERATIONAL VOLTAGE(UE) AT DC - MAX	0 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE(UE) AT AC - MAX	120 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
COLOR	Yellow
RATED IMPULSE WITHSTAND VOLTAGE(UIMP)	4000 V AC
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Continuous light
MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
LAMP TYPE	LED
LIFESPAN, ELECTRICAL	100,000 h
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
TYPE	Continuous light module
MOUNTING POSITION	As required
CURRENT CONSUMPTION	0.03 A, at 110/120 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27
VOLTAGE TYPE	AC
NUMBER OF MODULES	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
RATED INSULATION VOLTAGE(UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171323

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

