




SL4/SL7 SIGNAL TOWERS
171376


Overview


Specifications


Resources

Contact



171376

Eaton Moeller® series SL4 LED multistrobe light, w

How to buy

Photo is representative



Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.



171297

Eaton Moeller® series SL4 Base module;100-mm aluminum tube and foot



171303

Eaton Moeller® series SL4 Base module;for vertical mounting on one sides



171302

Eaton Moeller® series SL4 Base module;external fixing holes



171305

Eaton Moeller® series SL4 Base module;100 mm aluminum tube

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME

Eaton Moeller® series SL4 Multi-strobe light modu

CATALOG NUMBER

171376

Product specifications

>

MODEL CODE

SL4-FL24-W-M

EAN

4015081678211

PRODUCT LENGTH/DEPTH

43 mm

PRODUCT HEIGHT

75 mm

PRODUCT WIDTH

43 mm

PRODUCT WEIGHT

0.042 kg

CERTIFICATIONS

UL
UL report applies to both US and Canada
CSA-C22.2 No. 14-10
UL 508
CE
CSA-C22.2 No. 94-91
UL File No.: E29184
UL Category Control No.: NKCR
CSA Class No.: NKCR7
Certified by UL for use in Canada
IEC/EN 60529
IEC/EN 60947-5-1

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY

SL signal towers

ENCLOSURE COLOR

Black

RADIATION ANGLE

360 °

LEAKAGE CURRENT

0.003 A

OUTSIDE DIAMETER

43 mm

LIGHT MODULES

LED

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN

24 V

FLASHING FREQUENCY

1 - 2.6 Hz

LIGHT TYPE

Multistrobe light

DEGREE OF PROTECTION

IP66
NEMA 13

OVERVOLTAGE CATEGORY	III
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	24 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
COLOR	Other
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
FEATURES	Various strobe sequences
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Flash light
MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
LAMP TYPE	LED
LIFESPAN, ELECTRICAL	100,000 h
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
TYPE	<ul style="list-style-type: none"> • LED for effective signaling effect • Multi-strobe light module
MOUNTING POSITION	As required
CURRENT CONSUMPTION	0.048 - 0.068 A, at 24 V AC/DC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27
VOLTAGE TYPE	AC/DC
NUMBER OF MODULES	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
RATED INSULATION VOLTAGE (UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171376

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

