



SL4/SL7 SIGNAL TOWERS
171380



Overview




Specifications



Resources


Contact






171380

Eaton Moeller® series SL4 Acoustic module;120 VAC

How to buy





>

<

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

171297

Eaton Moeller® series SL4 Base module;100-mm aluminum tube and foot

171303

Eaton Moeller® series SL4 Base module;for vertical mounting on one sides

171302

Eaton Moeller® series SL4 Base module;external fixing holes

171305

Eaton Moeller® series SL4 Base module;100 mm aluminum tube

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME

Eaton Moeller® series SL4 Acoustic module

CATALOG NUMBER

171380

Product specifications

>

MODEL CODE

SL4-AP120

EAN

4015081679096

PRODUCT LENGTH/DEPTH

43 mm

PRODUCT HEIGHT

72 mm

PRODUCT WIDTH

43 mm

PRODUCT WEIGHT

0.046 kg

UL File No.: E29184

Certified by UL for use in Canada

CE

UL 508

IEC/EN 60947-5-1

IEC/EN 60529

UL Category Control No.: NKCR

CSA-C22.2 No. 14-10

UL report applies to both US and Canada

CSA Class No.: NKCR7

UL

CSA-C22.2 No. 94-91

CERTIFICATIONS

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY

SL signal towers

RATED OPERATIONAL CURRENT (IE) - MAX

21 A

LOUDNESS

80 dB

RADIATION ANGLE	360 °
LEAKAGE CURRENT	0.003 A
OUTSIDE DIAMETER	43 mm
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	110 V
FREQUENCY RATING	4000 Hz
ALARM TYPE	2 types of sound Continuous tone Tone adjustable Pulsed tone Internal sound setting, 1 pole DIP
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	0 V
DEGREE OF PROTECTION	NEMA 13 IP66
OVERVOLTAGE CATEGORY	III
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	0 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	120 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
COLOR	Black
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Continuous tone/pulse tone
MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
TYPE	Acoustic module
MOUNTING POSITION	As required Place only at the highest position on a pole
CURRENT CONSUMPTION	0.021 A, at 110/120 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27
VOLTAGE TYPE	AC
RATED INSULATION VOLTAGE (UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171380



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to

solve the world's most urgent power management challenges.