



SL4/SL7 SIGNAL TOWERS
171422



Overview



Specifications



Resources



Contact



171422

Eaton Moeller® series SL7 Strobe light module; rec



How to buy

Photo is representative



Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.



171450

Eaton Moeller® series SL7 Base module;for vertical mounting on one sides



171443

Eaton Moeller® series SL7 Base module;100-mm aluminum tube and foot



177351

Eaton Moeller® series SL7 Basic module, one-sided vertical mounting, max. 3 modules, M12A



171445

Eaton Moeller® series SL7 Base module;400-mm aluminum tube

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME	Eaton Moeller® series SL7 Strobe light module
--------------	---

CATALOG NUMBER	171422
----------------	--------

Product specifications

>

MODEL CODE	SL7-FL24-R-HP
------------	---------------

EAN	4015081679515
-----	---------------

PRODUCT LENGTH/DEPTH	73 mm
----------------------	-------

PRODUCT HEIGHT	73 mm
----------------	-------

PRODUCT WIDTH	73 mm
---------------	-------

PRODUCT WEIGHT	0.09 kg
----------------	---------

CERTIFICATIONS

CE
CSA Class No.: NKCR7
IEC/EN 60529
UL 508
CSA-C22.2 No. 94-91
IEC/EN 60947-5-1
UL report applies to both US and Canada
UL Category Control No.: NKCR
UL File No.: E29184
Certified by UL for use in Canada
CSA-C22.2 No. 14-10
UL

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	SL signal towers
------------------	------------------

ENCLOSURE COLOR	Black
-----------------	-------

RADIATION ANGLE	360 °
-----------------	-------

LEAKAGE CURRENT	0.003 A
-----------------	---------

OUTSIDE DIAMETER	73 mm
------------------	-------

LIGHT MODULES	High Performance LED
---------------	----------------------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	18 V
--	------

FLASHING FREQUENCY	1.4 Hz
--------------------	--------

LIGHT TYPE	Strobe light
------------	--------------

DEGREE OF PROTECTION	NEMA 4 IP66
----------------------	----------------

OVERVOLTAGE CATEGORY	III
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	18 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	30 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	26 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
COLOR	Red
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Flash light
MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
LAMP TYPE	LED
LIFESPAN, ELECTRICAL	50,000 h
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
TYPE	• High-performance LED for maximum signaling effect • Strobe light module
MOUNTING POSITION	As required
CURRENT CONSUMPTION	0.26 - 0.265 A, at 24 V AC/DC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27
VOLTAGE TYPE	AC/DC
NUMBER OF MODULES	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
RATED INSULATION VOLTAGE (UI)	250 V

Brochures

Catalogs

Certification reports


Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171422

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

