



SL4/SL7 SIGNAL TOWERS
171467


Overview


Specifications


Resources

Contact



171467

Eaton Moeller® series SL7 Continuous light modul

How to buy

Photo is representative



Photo is representative




Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

171450

Eaton Moeller® series SL7 Base module;for vertical mounting on one sides

171443

Eaton Moeller® series SL7 Base module;100-mm aluminum tube and foot

177351

Eaton Moeller® series SL7 Basic module, one-sided vertical mounting, max. 3 modules, M12A

171445

Eaton Moeller® series SL7 Base module;400-mm aluminum tube

View more

View less

GENERAL SPECIFICATIONS

General specifications

>

PRODUCTNAME Eaton Moeller® series SL7 Continuous light modu

CATALOG NUMBER 171467

Product specifications

>

MODEL CODE SL7-L120-B

EAN 4015081677948

PRODUCT LENGTH/DEPTH 73 mm

PRODUCT HEIGHT 73 mm

PRODUCT WIDTH 73 mm

PRODUCT WEIGHT 0.082 kg

COMPLIANCES CE Marked

CERTIFICATIONS

CSA Certified
UL Listed
UL 508
cULus Listed
CSA Std. C22.2 No. 14-10
UL Listed file E29184
CSA Class No. NKCR7
CSA Std. C22.2 No. 94-91
IEC Rated
UL
UL File No.: E29184
CSA Class No.: NKCR7
CSA-C22.2 No. 14-10
Certified by UL for use in Canada
IEC/EN 60529
CSA-C22.2 No. 94-91
CE

CATALOG NOTES	0
PRODUCT SPECIFICATIONS	
PRODUCT CATEGORY	SL signal towers
ENCLOSURE COLOR	Black
RADIATION ANGLE	360 °
LEAKAGE CURRENT	0.003 A
ENCLOSURE	UL type 4, 4X, 13
OUTSIDE DIAMETER	73 mm
LIGHT MODULES	LED
RATED OPERATIONAL VOLTAGE(UE) AT AC - MIN	110 V
LIGHT TYPE	Continuous light
ENVIRONMENTAL RATING	IP66
ILLUMINATION	Continuous LED
VOLTAGE RATING	110/120 Vac
DEGREE OF PROTECTION	NEMA 4X IP66
OVERVOLTAGE CATEGORY	III
RATED OPERATIONAL VOLTAGE(UE) AT DC - MIN	0 V
RATED OPERATIONAL VOLTAGE(UE) AT DC - MAX	0 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE(UE) AT AC - MAX	120 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
COLOR	Blue
RATED IMPULSE WITHSTAND VOLTAGE(UIMP)	4000 V AC
QUANTITY	1
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Continuous light

MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
LAMP TYPE	LED
LIFESPAN, ELECTRICAL	100,000 h
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
SERIES	SL7
TYPE	Continuous light module
MOUNTING POSITION	As required
CURRENT CONSUMPTION	0.028 - 0.031 A, at 110/120 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms
VOLTAGE TYPE	AC
NUMBER OF MODULES	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
RATED INSULATION VOLTAGE (UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

Specifications and datasheets



[Contact me](#)

171467

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.