



SL4/SL7 SIGNAL TOWERS
171473


Overview


Specifications


Resources

Contact



Photo is representative




Photo is representative

171473

Eaton Moeller® series SL7 Continuous light modul

How to buy




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.



171450

Eaton Moeller® series SL7 Base module;for vertical mounting on one sides



171443

Eaton Moeller® series SL7 Base module;100-mm aluminum tube and foot



177351

Eaton Moeller® series SL7 Basic module, one-sided vertical mounting, max. 3 modules, M12A



171445

Eaton Moeller® series SL7 Base module;400-mm aluminum tube

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME	Eaton Moeller® series SL7 Continuous light modu
--------------	---

CATALOG NUMBER	171473
----------------	--------

Product specifications

>

MODEL CODE	SL7-L230-B
------------	------------

EAN	4015081677993
-----	---------------

PRODUCT LENGTH/DEPTH	73 mm
----------------------	-------

PRODUCT HEIGHT	73 mm
----------------	-------

PRODUCT WIDTH	73 mm
---------------	-------

PRODUCT WEIGHT	0.082 kg
----------------	----------

CERTIFICATIONS

CSA-C22.2 No. 14-10
UL Category Control No.: NKCR
CSA Class No.: NKCR7
UL report applies to both US and Canada
CE
IEC/EN 60529
UL
IEC/EN 60947-5-1
CSA-C22.2 No. 94-91
UL File No.: E29184
Certified by UL for use in Canada
UL 508

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	SL signal towers
------------------	------------------

ENCLOSURE COLOR	Black
-----------------	-------

RADIATION ANGLE	360 °
-----------------	-------

LEAKAGE CURRENT	0.003 A
-----------------	---------

OUTSIDE DIAMETER	73 mm
------------------	-------

LIGHT MODULES	LED
---------------	-----

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	230 V
--	-------

LIGHT TYPE	Continuous light
------------	------------------

DEGREE OF PROTECTION	IP66 NEMA 4
----------------------	----------------

OVERVOLTAGE CATEGORY	III
----------------------	-----

RATED OPERATIONAL VOLTAGE(UE) AT DC - MIN	0 V
RATED OPERATIONAL VOLTAGE(UE) AT DC - MAX	0 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE(UE) AT AC - MAX	240 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
COLOR	Blue
RATED IMPULSE WITHSTAND VOLTAGE(UIMP)	4000 V AC
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Continuous light
MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
LAMP TYPE	LED
LIFESPAN, ELECTRICAL	100,000 h
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
TYPE	Continuous light module
MOUNTING POSITION	As required
CURRENT CONSUMPTION	0.027 - 0.028 A, at 230/240 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms
VOLTAGE TYPE	AC
NUMBER OF MODULES	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
RATED INSULATION VOLTAGE(UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171473

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

