

United States Select your location

Search parts, catalogs

Sign in

We make what matters work*

Products Digital Services Markets Support Company

Search

Toggle Mobile Menu

Search

Search

Products

Close Search

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)
- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)
- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)
- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

Digital

Close Search

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)
- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)
- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)
- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)
- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



MSC motor starters combinations
101045

[Overview](#) [Specifications](#) [Resources](#)

How to buy

Back to search

[Download](#) Zoom

Photo is representative

[Download](#) Zoom

Photo is representative

[Download](#) Zoom

Photo is representative

[Download](#) Zoom

Photo is representative

PreviousNext

DownloadZoom

- 
- 
- 
- 

PreviousNext

101045

Eaton Moeller® series MSC-D DOL starter, 380 V 400 V 415 V: 3, 4 kW, Ir= 6.3 - 10 A, 230 V 50 Hz, 240 V 60 Hz, AC

[Add a free sample to the cart](#) [How to buy](#)

- [Configurator Motor starter combinations](#)

×



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

Keep My Cart

Create a New Cart

×



Item is already in the cart.

Okay

Photo is representative

- General specifications
- Product specifications

General specifications

Product Name
Eaton Moeller® series MSC-D DOL starter

Catalog Number
101045

Model Code
MSC-D-10-M17(230V50HZ)

EAN
4015081009404

Product Length/Depth
123.4 mm

Product Height
228 mm

Product Width
45 mm

Product Weight
0.87 kg

Certifications
VDE 0660
UL 60947-4-1
CSA
IEC/EN 60947-4-1
CSA Class No.: 3211-24
UL Category Control No.: NLRV
CE
CSA File No.: 012528
CSA-C22.2 No. 60947-4-1-14
UL
UL File No.: E36332

Product specifications

Rated operational current for specified heat dissipation (In)
10 A

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated operational power at AC-3, 380/400 V, 50 Hz
4 kW

Rated operational voltage
230 - 415 V AC

Rated conditional short-circuit current, type 1, 480 Y/277 V
0 A

Rated control supply voltage (Us) at AC, 50 Hz - min
230 V

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting method
DIN rail

10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

Rated power at 575 V, 60 Hz, 3-phase
0 kW

Rated power at 460 V, 60 Hz, 3-phase
0 kW

10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

Rated control supply voltage (Us) at DC - min
0 V

Fitted with:
Short-circuit release
Number of pilot lights
0

Rated control supply voltage (Us) at AC, 50 Hz - max
230 V

Coordination type
2

10.8 Connections for external conductors
Is the panel builder's responsibility.
Coordination class (IEC 60947-4-3)
Class 2

Rated conditional short-circuit current, type 1, 600 Y/347 V
0 A

Power consumption, sealing, 50 Hz
2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Ambient operating temperature - max
55 °C

Rated operational power at AC-3, 220/230 V, 50 Hz
2.2 kW

Connection to SmartWire-DT
No

Number of command positions
0

Static heat dissipation, non-current-dependent Pvs
2.1 W

Electrical connection type of main circuit
Screw connection

Electrical connection type for auxiliary- and control-current circuit
Screw connection

Rated control supply voltage (Us) at DC - max
0 V

10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

Ambient operating temperature - min
-25 °C

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

Class
CLASS 10 A

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.3 Degree of protection of assemblies
Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent Pvid
2.6 W

Actuating voltage
230 V 50 Hz
240 V 60 Hz

Voltage type
AC

Switching capacity (auxiliary contacts, general use)
1 A, 250 VDC, (UL/CSA)

15 A, 600 V AC, (UL/CSA)
Overload release current setting - min
6.3 A
Equipment heat dissipation, current-dependent P_{vid}
7.8 W
Heat dissipation capacity P_{diss}
0 W
Rated operational current (I_e)
8.5 A
Suitable for
Also motors with efficiency class IE3
Number of auxiliary contacts (normally closed contacts)
0
Rated conditional short-circuit current (I_q), type 2, 380 V, 400 V, 415 V
50000 A
Power consumption
2.1 W
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects
Meets the product standard's requirements.
Overload release current setting - max
10 A
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.
Overvoltage category
III
Degree of protection
IP00
NEMA Other
Pollution degree
3
Rated control supply voltage (U_s) at AC, 60 Hz - min
0 V
10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.
Rated impulse withstand voltage (U_{imp})
6000 V AC
Connection
Screw terminals
10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
Functions
Temperature compensated overload protection
Rated conditional short-circuit current (I_q), type 2, 230 V
50000 A
Type
Starter with Bi-Metal release
10.2.2 Corrosion resistance
Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.
10.2.7 Inscriptions
Meets the product standard's requirements.
Short-circuit release (I_{rm}) - max
155 A
Rated control supply voltage (U_s) at AC, 60 Hz - max
0 V
Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V
10 A
Model
Direct starter
Number of auxiliary contacts (normally open contacts)
1
Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)
P300, DC operated (UL/CSA)
Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Brochures

- [Motor Starters in System xStart - brochure](#)
- [Save time and space thanks to the new link module PKZM0-XDM32ME](#)
- [Simple, flexible and safe! Distribution system for motor-starter combinations](#)

Download all files

Catalogs

- [Product Range Catalog Switching and protecting motors](#)

Declarations of conformity

- [DA-DC-00004911.pdf](#)
- [DA-DC-00004879.pdf](#)

Drawings

- [eaton-manual-motor-starters-starter-msc-d-dol-starter-dimensions.eps](#)
- [eaton-manual-motor-starters-mounting-msc-d-dol-starter-3d-drawing.eps](#)
- [eaton-general-ie-ready-dilm-contactor-standards.eps](#)
- [eaton-manual-motor-starters-dol-starter-msc-d-3d-drawing.eps](#)

Download all files

eCAD model

- [DA-CE-ETN.MSC-D-10-M17\(230V50HZ\)](#)

Installation instructions

- [IL03402010Z](#)

Installation videos

- [WIN-WIN with push-in technology](#)

mCAD model

- [DA-CD-msc_d_bg2](#)
- [DA-CS-msc_d_bg2](#)

Download all files

Wiring diagrams

- [eaton-manual-motor-starters-device-msc-d-dol-starter-wiring-diagram.eps](#)

Export product specification

-





Enter your city, state, or zip code or [Locate me](#)

Search

Show locations that offer:

- ☐ Product pickup
- ☐ Order online and ship product

- 101045

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we’re accelerating the planet’s transition to renewable energy and helping to solve the world’s most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

Back to top of the page

Are you sure?

Cancel Sign out

Are you sure?

Cancel Sign out

