

[United States](#) [Select your location](#)

[Sign in](#)

We make what matters work\*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

Search

[Products](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)
  
- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)
  
- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)
  
- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

#### [Services](#)

Close Search

#### [Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)
  
- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)
  
- [Vehicles](#)

#### [Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

#### [Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)
  
- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)
  
- [Selling to Eaton](#)

#### [MyEaton](#)

Close Search

#### Quick links



PKE electronic motor protection circuit breaker  
168797

[Overview](#) [Specifications](#) [Resources](#)

How to buy

[Back to search](#)

[Download](#) Zoom

Download Zoom

# 168797

Eaton Moeller® series PKE Trip block, 15 - 36 A, Systemprotection, Connection to SmartWire-DT: yes, For use with: PKE65 basic device  
[Add a free sample to the cart](#) [How to buy](#)

×



## Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

Keep My Cart

Create a New Cart

×



## Item is already in the cart.

Okay

- [General specifications](#)
- [Product specifications](#)

### General specifications

Product Name  
Eaton Moeller® series PKE Trip block  
Catalog Number  
168797  
Model Code  
PKE-XTUWACP-36  
EAN  
4015081652884  
Product Length/Depth  
84.4 mm  
Product Height  
69.9 mm  
Product Width  
55 mm  
Product Weight  
0.196 kg  
Certifications

## Product specifications

Rated operational current for specified heat dissipation ( $I_n$ )

36 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Ambient operating temperature (enclosed) - min

25 °C

Rated control supply voltage ( $U_s$ ) at AC, 50 Hz - min

0 V

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Cut-out periods - min

≤ 500 ms, main conducting paths, AC-4 cycle operation

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Ambient operating temperature (enclosed) - max

40 °C

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Ambient storage temperature - min

40 °C

Rated control supply voltage ( $U_s$ ) at DC - min

0 V

Current flow times - min

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

1000 (Class 20) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

500 (Class 5) AC-4 cycle operation, Main conducting paths

Rated control supply voltage ( $U_s$ ) at AC, 50 Hz - max

0 V

10.8 Connections for external conductors

Is the panel builder's responsibility.

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Ambient operating temperature - max

55 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Connection to SmartWire-DT

In conjunction with PKE-SWD-SP SmartWire DT PKE module

Yes

Static heat dissipation, non-current-dependent  $P_{vs}$

0 W

Rated control supply voltage ( $U_s$ ) at DC - max

0 V

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Number of poles

Three-pole

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Rated uninterrupted current ( $I_u$ )

36 A  
Short-circuit release  
Delayed approx. 60 ms, Trip blocks  
Trip block adjustable 5 - 8 x I<sub>r</sub>  
75 A - 288 A, I<sub>rm</sub>, Setting range  
± 20% tolerance, Trip blocks

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.3 Degree of protection of assemblies  
Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent P<sub>vid</sub>  
1.7 W

Operating frequency  
60 Operations/h  
Voltage type  
Self powered  
Short-circuit release function  
Delayed  
Product category  
Accessories  
Overload release current setting - min  
15 A  
Equipment heat dissipation, current-dependent P<sub>vid</sub>  
4.9 W  
Heat dissipation capacity P<sub>diss</sub>  
0 W  
Rated operational current (I<sub>e</sub>)  
36 A  
Temperature compensation  
-25 - 55 °C, Operating range  
-5 - 40 °C to IEC/EN 60947, VDE 0660  
Rated frequency - min  
50 Hz

10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  
Meets the product standard's requirements.

Overload release current setting - max  
36 A

10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

Degree of protection  
Terminals: IP00  
Device: IP20  
Overvoltage category  
III  
Rated frequency - max  
60 Hz  
Ambient storage temperature - max  
80 °C  
Rated operational voltage (U<sub>e</sub>) at AC - max  
690 V  
Undelayed short-circuit release - min  
75 A  
Pollution degree  
3  
Rated control supply voltage (U<sub>s</sub>) at AC, 60 Hz - min  
0 V

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.  
Rated impulse withstand voltage (U<sub>imp</sub>)

6000 V AC  
10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  
Functions  
Line and cable protection  
Overcurrent protection  
System protection  
Short-circuit protection  
Protection type  
Electronic release  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.  
10.2.7 Inscriptions  
Meets the product standard's requirements.  
Rated control supply voltage (Us) at AC, 60 Hz - max  
0 V  
Undelayed short-circuit release - max  
288 A  
Shock resistance  
25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
Altitude  
Max. 2000 m  
Serial Number Verified :  
Authenticated: ✓  
The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

## Brochures

- [Motor Starters in System xStart - brochure](#)
- [Motor-Protective Circuit-Breaker PKE - brochure](#)
- [PKE – Communication module Modbus RTU](#)

Download all files

## Catalogs

- [Product Range Catalog Switching and protecting motors](#)

## Certification reports

- [DA-DC-00004108.pdf](#)
- [DA-DC-00004544.pdf](#)
- [DA-DC-00004244.pdf](#)
- [DA-DC-00004545.pdf](#)

## Characteristic curve

- [eaton-manual-motor-starters-pke65-characteristic-curve-006.eps](#)

## Declarations of conformity

- [DA-DC-00004945.pdf](#)
- [DA-DC-00004935.pdf](#)
- [DA-DC-00004944.pdf](#)
- [DA-DC-00004962.pdf](#)
- [DA-DC-00004950.pdf](#)

## Drawings

- [eaton-manual-motor-starters-mounting-3d-drawing.eps](#)
- [eaton-manual-motor-starters-pke-trip-block-3d-drawing-002.eps](#)

Download all files

## eCAD model

- [DA-CE-ETN.PKE-XTUWACP-36](#)

## Installation instructions

- [IL034013ZU](#)

## Installation videos

- [Video Motor Protective Circuit Breaker PKE](#)
- [WIN-WIN with push-in technology](#)

## Manuals and user guides

- [MN03402004Z\\_DE\\_EN](#)

## mCAD model

- [DA-CD-pke\\_xtua\\_65](#)
- [DA-CS-pke\\_xtua\\_65](#)

Download all files

## [Export product specification](#)

- 

x



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- Product pickup
- Order online and ship product

- 168797

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)

- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

**Let's talk big ideas**

- 
- 
- 
- 

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

[Back to top of the page](#)

Are you sure?

[Cancel](#) [Sign out](#)

Are you sure?

[Cancel](#) [Sign out](#)

[×](#)

[×](#)