



PKZ MOTOR PROTECTION CIRCUIT BREAKER
088911



Overview



Specifications



Resources

How to





Photo is representative

Photo is representative



088911

Eaton Moeller® series PKZM0 Transformer-protected
Ir=0.63-1A, screw connection

How to buy



Learn about our Push-in terminals



Configure Motor Start Combination




Photo is representative



Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

082882

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

072896

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals

032720

Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0

219654

Eaton Moeller® series CI-K Insulation enclosure, for PKZ0, 160 x 100 x 100 +rotary handle, black/grey

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications



PRODUCT NAME	Eaton Moeller® series PKZM0 Transformer-protective switch
CATALOG NUMBER	088911
MODEL CODE	PKZM0-1-T
EAN	4015080889113
PRODUCT LENGTH/DEPTH	76 mm
PRODUCT HEIGHT	93 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.245 kg
CERTIFICATIONS	IEC/EN 60947 VDE 0660

Product specifications



PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	1 A
--	-----

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (1 - 6) mm ² , ferrule to DIN 46228 2 x (1 - 6) mm ² , ferrule to DIN 46228
--	--

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
-----------------------------------	--

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 440 V AC	150 kA
--	--------

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
---	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
--	--

Mounting Method	DIN rail (top hat rail) mounting optional
------------------------	---

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be handled as a unit.
-----------------------	--

ADJUSTMENT RANGE SHORT-TERM DELAYED SHORT-CIRCUIT RELEASE - MAX	0 A
--	-----

SWITCHING CAPACITY	1 A (3 contacts in series), DC-5 up to 250V 1 A, AC-3 up to 690 V
---------------------------	--

STRIPPING LENGTH (MAIN CABLE)	10 mm
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	150 kA
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
FITTED WITH:	Switched-off indicator
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MAX	20 A
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ADJUSTMENT RANGE SHORT-TERM DELAYED SHORT-CIRCUIT RELEASE - MIN	0 A
PROTECTION	Finger and back-of-hand proof, Protection against direct actuated from front (EN 50274)
ACTUATOR TYPE	Turn button
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT	Other
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
DEVICE CONSTRUCTION	Built-in device fixed built-in technique
FEATURES	Complete device with protection unit Phase-failure sensitivity (according to IEC/EN 60947-2 Part 102)
LIFESPAN, ELECTRICAL	100,000 operations
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
NUMBER OF POLES	Three-pole
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 690 V AC	150 kA
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be certified as a whole.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be certified as a whole.
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 4/8

RATED UNINTERRUPTED CURRENT (IU)

1 A

SHORT-CIRCUIT RELEASE

Basic device, fixed 20 x I_u, Trip Blocks
 $\pm 20\%$ tolerance, Trip blocks
 20 A, I_{rm}, Setting range max.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the instruction leaflet (IL) is observed.

10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to

10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL

Is the panel builder's responsibility.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES

Does not apply, since the entire switchgear needs to

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID

1.62 W

OPERATING FREQUENCY

40 Operations/h

PRODUCT CATEGORY

Transformer protective circuit breaker

OVERLOAD RELEASE CURRENT SETTING - MIN

0.63 A

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC

150 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 440 V AC

150 kA

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID

4.86 W

HEAT DISSIPATION CAPACITY PDISS

0 W

RATED OPERATIONAL CURRENT (IE)

1 A

SUITABLE FOR

DIN rail (top hat rail) mounting
 Also motors with efficiency class IE3

TEMPERATURE COMPENSATION

-25 - 55 °C, Operating range
 $\leq 0.25\%/\text{K}$, residual error for T > 40°
 -5 - 40 °C to IEC/EN 60947, VDE 0660

TERMINAL CAPACITY (SOLID)

1 x (1 - 6) mm²
 2 x (1 - 6) mm²

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)

0

RATED FREQUENCY - MIN

50 Hz

SHORT-CIRCUIT CURRENT

60 kA DC, up to 250 V DC, Main conducting path

POWER LOSS

4.86 W

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

LIFESPAN, MECHANICAL	100,000 Operations
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
OVERLOAD RELEASE CURRENT SETTING - MAX	1 A
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 500 V AC	150 kA
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	Terminals: IP00 IP20
RATED FREQUENCY - MAX	60 Hz
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MIN	20 A
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
CONNECTION	Screw terminals
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
FUNCTIONS	Transformer protection For the protection of transformers with a high inrush
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable 1 Nm, Screw terminals, Control circuit cables
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 500 V AC	150 kA
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 690 V AC	150 kA

SHOCK RESISTANCE

shock 10 ms

RATED OPERATIONAL VOLTAGE (UE) - MAX

690 V

ALTITUDE

Max. 2000 m

Brochures

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Installation videos

Manuals and user guides

mCAD model

Wiring diagrams

088911



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to

help our customers manage power—today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.