



PKZ MOTOR PROTECTION CIRCUIT
BREAKER
088913


Overview


Specifications


Resources

How to buy




Photo is representative






Photo is representative

088913

Eaton Moeller® series PKZM0 Transformer-protect
Ir=1.6-2.5A, screw connection

How to buy

-  [Learn about our Push-in terminals](#)
-  [Configure Motor Start Combination](#)




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

082882

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

072896

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals

032720

Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0

219654

Eaton Moeller® series CI-K Insulation enclosure, for PKZ0, 160 x 100 mm, +rotary handle, black/grey

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications	>	PRODUCT NAME	Eaton Moeller® series PKZM0 Transformer-protecti
		CATALOG NUMBER	088913
Product specifications	>	MODEL CODE	PKZM0-2,5-T
		EAN	4015080889137
		PRODUCT LENGTH/DEPTH	76 mm
		PRODUCT HEIGHT	93 mm
		PRODUCT WIDTH	45 mm
		PRODUCT WEIGHT	0.282 kg
		CERTIFICATIONS	IEC/EN 60947 VDE 0660

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	2.5 A
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (1 - 6) mm², ferrule to DIN 46228 1 x (1 - 6) mm², ferrule to DIN 46228
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 440 V AC	150 kA
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
MOUNTING METHOD	DIN rail (top hat rail) mounting optional
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
ADJUSTMENT RANGE SHORT-TERM DELAYED SHORT-CIRCUIT RELEASE - MAX	0 A
SWITCHING CAPACITY	2.5 A (3 contacts in series), DC-5 up to 250V 2.5 A, AC-3 up to 690 V

STRIPPING LENGTH (MAIN CABLE)	10 mm
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	150 kA
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
FITTED WITH:	Switched-off indicator
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MAX	50 A
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ADJUSTMENT RANGE SHORT-TERM DELAYED SHORT-CIRCUIT RELEASE - MIN	0 A
PROTECTION	Finger and back-of-hand proof, Protection against di- actuated from front (EN 50274)
ACTUATOR TYPE	Turn button
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT	Other
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
DEVICE CONSTRUCTION	Built-in device fixed built-in technique
FEATURES	Complete device with protection unit Phase-failure sensitivity (according to IEC/EN 60947-1 Part 102)
LIFESPAN, ELECTRICAL	100,000 operations
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
NUMBER OF POLES	Three-pole
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 690 V AC	5 kA
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with

MOUNTING POSITION	height.
RATED UNINTERRUPTED CURRENT (IU)	2.5 A
SHORT-CIRCUIT RELEASE	± 20% tolerance, Trip blocks Basic device, fixed 20 x Iu, Trip Blocks 50 A, Im, Setting range max.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the inf instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.57 W
OPERATING FREQUENCY	40 Operations/h
PRODUCT CATEGORY	Transformer protective circuit breaker
OVERLOAD RELEASE CURRENT SETTING - MIN	1.6 A
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC	150 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 440 V AC	150 kA
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4.71 W
HEAT DISSIPATION CAPACITY PDISS	0 W
RATED OPERATIONAL CURRENT (IE)	2.5 A
SUITABLE FOR	Also motors with efficiency class IE3 DIN rail (top hat rail) mounting
TEMPERATURE COMPENSATION	-25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660 ≤ 0.25 %/K, residual error for T > 40°
TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
RATED FREQUENCY - MIN	50 Hz
SHORT-CIRCUIT CURRENT	60 kA DC, up to 250 V DC, Main conducting path
POWER LOSS	4.71 W
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.

LIFESPAN, MECHANICAL	100,000 Operations
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
OVERLOAD RELEASE CURRENT SETTING - MAX	2.5 A
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 500 V AC	150 kA
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	Terminals: IP00 IP20
RATED FREQUENCY - MAX	60 Hz
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MIN	50 A
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
CONNECTION	Screw terminals
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device
FUNCTIONS	Transformer protection For the protection of transformers with a high inrush
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable 1 Nm, Screw terminals, Control circuit cables
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 500 V AC	150 kA
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 690 V AC	5 kA

help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.