

# Eaton 189637

Catalog Number: 189637

NZMH4-PX800-TAZ-AVE. NZM4 PXR25 circuit breaker - integrated energy measurement class 1, 800A, 3p, Screw terminal, earth-fault protection, ARMS and zone selectivity

## General specifications



Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker electronic	189637
Model Code	NZMH4-PX800-TAZ-AVE
EAN	Product Length/Depth
4015081875849	501 mm
Product Height	Product Width
280 mm	260 mm
Product Weight	Compliances
29 kg	RoHS conform
Certifications	
IEC	
IEC/EN 60947	

## Product specifications

Rated operational current for specified heat dissipation (In)

800 A

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

37 kA

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### Mounting Method

Withdrawable

Built-in device slide-in technique (withdrawable)

#### Amperage Rating

800 A

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### Terminal capacity (copper strip)

Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal

10 segments of 50 mm x 1 mm (2x) at 1-hole module plate

10 segments of 80 mm x 1 mm (2x) at rear-side width extension

Min. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)

Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal

Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched)

#### Handle type

Rocker lever

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### Ambient storage temperature - min

40 °C

#### Earth-fault current setting (Ig) - max

800 x In

## Resources

### Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

### Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-022.eps](#)

[eaton-circuit-breaker-withdrawable-unit-nzm-mccb-dimensions.eps](#)

### Installation instructions

[IL012101ZU](#)

### Installation videos

[Introduction of the new digital circuit breaker NZM](#)

### The new digital NZM Range

#### mCAD model

[DA-CS-nzm4\\_3p](#)

[DA-CD-nzm4\\_3p](#)

#### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

## Protection against direct contact

Finger and back-of-hand proof to VDE 0106 part 100

## Terminal capacity (copper busbar)

Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate

50 mm x 10 mm (2x) at rear-side 2-hole module plate

M10 at rear-side screw connection

Max. 80 mm x 10 mm (2x) at rear-side width extension

Max. 50 mm x 10 mm (2x) direct at switch rear-side connection

Min. 60 mm x 10 mm at rear-side width extension

Min. 25 mm x 5 mm direct at switch rear-side connection

Min. 25 mm x 5 mm at rear-side 1-hole module plate

## 10.8 Connections for external conductors

Is the panel builder's responsibility.

## Special features

LSIG overload protection and delayed and non-delayed short-circuit protective device, earth-fault protection Class 1 energy measurement, r.m.s. value measurement, and "thermal memory"

USB interface for configuration and test function with Power

Xpert Protection Manager software Zone selectivity ZSI

Maintenance Mode ARMS Interface module in equipment

supplied. Optionally communication-capable with internal

Modbus RTU module or CAM Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity  $I_{cn}$ ) Rated current = rated uninterrupted current: 800 A

## Ambient operating temperature - max

70 °C

## Position of connection for main current circuit

Connection at separate chassis part

## Rated insulation voltage (Ui)

1000 V AC

## Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

## Terminal capacity (copper stranded conductor/cable)

50 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) direct at switch rear-side connection

120 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) direct at switch rear-side connection

## Features

Motor drive optional

Protection unit

Lifespan, electrical

3000 operations at 415 V AC-1

2000 operations at 690 V AC-1

3000 operations at 400 V AC-1

**Electrical connection type of main circuit**

Other

**Short-circuit total breaktime**

< 25 ms (< 415 V); < 35 ms (> 415 V)

**Rated impulse withstand voltage (Ui<sub>imp</sub>) at main contacts**

8000 V

**Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz**

50 kA

**10.9.3 Impulse withstand voltage**

Is the panel builder's responsibility.

**Utilization category**

B (IEC/EN 60947-2)

**Number of poles**

Three-pole

**Ambient operating temperature - min**

-25 °C

**10.6 Incorporation of switching devices and components**

Does not apply, since the entire switchgear needs to be evaluated.

**10.5 Protection against electric shock**

Does not apply, since the entire switchgear needs to be evaluated.

**Terminal capacity (control cable)**

0.75 mm<sup>2</sup> - 1.5 mm<sup>2</sup> (2x)

0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> (1x)

**Equipment heat dissipation, current-dependent**

79 W

**Instantaneous current setting (li) - min**

2 A

**10.13 Mechanical function**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**10.2.6 Mechanical impact**

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 230 V, 50/60 Hz

63 kA

#### Application

690 V

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Rated short-circuit making capacity  $I_{cm}$  at 240 V, 50/60 Hz

275 kA

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 440 V, 50/60 Hz

50 kA

#### Short-circuit release delayed setting - max

10 A

#### Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

Rated short-circuit making capacity  $I_{cm}$  at 525 V, 50/60 Hz

143 kA

Rated short-circuit making capacity  $I_{cm}$  at 690 V, 50/60 Hz

100 kA

#### Instantaneous current setting (I<sub>i</sub>) - max

18 A

#### Overload current setting (I<sub>r</sub>) - min

320 A

#### Short delay current setting (I<sub>sd</sub>) - min

2 A

#### Number of auxiliary contacts (normally closed contacts)

0

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### Lifespan, mechanical

10000 operations

Overload current setting (Ir) - max

800 A

Voltage rating

690 V - 690 V

Terminal capacity (copper solid conductor/cable)

95 mm<sup>2</sup> - 185 mm<sup>2</sup> (2x) at rear-side 2-hole module plate

35 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) at rear-side 2-hole module plate

95 mm<sup>2</sup> - 300 mm<sup>2</sup> (2x) at rear-side 1-hole module plate

300 mm<sup>2</sup> (4x) at rear-side width extension

95 mm<sup>2</sup> - 240 mm<sup>2</sup> (6x) at rear-side width extension

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (4x) at 4-hole tunnel terminal

120 mm<sup>2</sup> - 300 mm<sup>2</sup> (1x) at rear-side 1-hole module plate

Degree of protection (terminations)

IP00 (terminations, phase isolator and strip terminal)

IP10 (tunnel terminal)

Short-circuit release delayed setting - min

2 A

Terminal capacity (aluminum stranded conductor/cable)

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (4x) at 4-hole tunnel terminal

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Short-circuit release non-delayed setting - min

2 A

Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

Overvoltage category

III

Rated short-time withstand current (t = 1 s)

19.2 kA

Short delay current setting (Isd) - max

10 A

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Earth-fault current setting (Ig) - min

160 x In

Number of auxiliary contacts (change-over contacts)

0

Rated short-time withstand current (t = 0.3 s)

19.2 kA

#### Accessories required

NZM4-XAVS

#### Ambient storage temperature - max

70 °C

#### Release system

Electronic release

#### Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz

50 kA

#### Optional terminals

Connection on rear. Strip terminal. Tunnel terminal

#### Pollution degree

3

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### Functions

Earth-fault protection

Systems, cable, selectivity and generator protection

ARMS maintenance mode

Zone selectivity

Integrated earth fault protection

#### Short-circuit release non-delayed setting - max

18 A

#### Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

187 kA

#### Standard terminals

Screw connection

#### Type

Circuit breaker

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

Rated short-circuit making capacity  $I_{cm}$  at 440 V, 50/60 Hz

187 kA

Number of auxiliary contacts (normally open contacts)

0

**Isolation**

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

Number of operations per hour - max

60

Circuit breaker frame type

NZM4

Direction of incoming supply

As required

Shock resistance

15 g (half-sinusoidal shock 11 ms)



Eaton Corporation plc

Eaton House

30 Pembroke Road  
Dublin 4, Ireland

Eaton.com

© 2023 Eaton. All Rights  
Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



Eaton.com/socialmedia