



LITELINE G2 IP44

Liteline IP44 Generation 2. Powerful fluorescent tube replacement with patented folding end caps in recycled plastic. By replacing traditional fluorescent luminaires you not only reduce your energy consumption but also considerably reduce maintenance costs. With Liteline G2 IP44, you get a replaceable LED and driver, as well as the possibility of choosing colour temperature and adjusting lumen output via DIP-switch. The luminaire comes in two lengths with a number of control possibilities. Supplied with a prismatic cover of recycled, durable polycarbonate with an opal diffuser for even light distribution. All our Liteline G2 luminaires are equipped with quick terminals at both ends for simple through wiring. Through wiring 5x2,5mm² as standard. There are also cable bushings in both ends, as well as in the base of the luminaire. Liteline G2 is perfect where the light requirement is great and the quality requirement is high, such as production environments, garages or storage areas.




- **Energy-efficient fluorescent tube replacement, now with even higher efficiency – up to 159lm/W**
- **Replaceable LED and driver – built for the future**
- **Prismatic diffuser in durable (IK10) recycled plastic with pre-installed opal film.**
- **Patented folding end caps in recycled plastic for easy installation**
- **Selectable colour temperature and adjustable lumen output via DIP-switch.**
- **Luminaire life time L80 100,000h Ta 25°C**
- **Life time CLO L100 100,000h Ta 25°C**
- **Driver life time 100,000h/10%**



LITELINE G2 IP44 600






GTIN	Type	Colour temperature	Luminaire lumen	Luminaire efficiency	Effect luminaire
7392971149240	On/Off	3000K/4000K	2700-4400lm	<157lm/W	18-28W
7392971149257	¹⁾ Microwave sensor	3000K/4000K	2700-4400lm	<157lm/W	18-28W
7392971149264	¹⁾ SC Microwave sensor, basic lighting	3000K/4000K	2700-3800lm	<158lm/W	18-24W
7392971149271	^{2,3)} Bluetooth	3000K/4000K	2700-4400lm	<157lm/W	18-28W
7392971149288	^{3,4)} DALI	3000K/4000K	2700-4400lm	<157lm/W	18-28W



LITELINE G2 IP44 1200



GTIN	Type	Colour temperature	Luminaire lumen	Luminaire efficiency	Effect luminaire
7392971149301	On/Off	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149318	¹⁾ Microwave sensor	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149325	¹⁾ SC Microwave sensor, basic lighting	3000K/4000K	3900-5400lm	<159lm/W	25-34W
7392971149332	^{3,4)} Bluetooth	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149349	^{2,4)} DALI	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149806	^{2,4,6)} DALI, CLO	3000K/4000K	5650lm	<141lm/W	35-40W
7392971149356	⁵⁾ On/Off, Emergency lighting	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149363	^{1,5)} Microwave sensor, Emergency lighting	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149370	^{1,5)} SC Microwave sensor, grundljus, Emergency lighting	3000K/4000K	3900-5400lm	<159lm/W	25-34W
7392971149387	^{3,4,5)} Bluetooth, Emergency lighting	3000K/4000K	3700-6300lm	<158lm/W	25-40W
7392971149394	^{2,4,5)} DALI, Emergency lighting	3000K/4000K	3700-6300lm	<158lm/W	25-40W



ACCESSORIES



GTIN	Type
7392971147727	Emergency Lighting Module Liteline G2
7392971145648	Emergency light battery Li-Ion 3,2V 3,2Ah 1,5h