



LITELINE BASIC IP44

Industrial luminaire IP44 in basic model, replaces T5 and T8 luminaires with lower energy consumption and reduced maintenance. The luminaire has a line prismatic diffuser in impact resistant PC with opal film and smart patented folding end caps. Push-in terminal, through wiring, one bushing in each end cap and two in the middle, one of which is centred, for concealed cable routing. Perfect when you are looking for a simple solution that does the job – basement storage, laundry rooms or simple industrial premises. Adjustable lumen output and wattage via DIP-switch Power (1200).

- Energy-efficient fluorescent tube replacement, now in two lengths: 600 and 1200
- Linear prismatic diffuser in impact resistant (IK10) plastic with opal film
- Folding patented end caps for easy installation
- DIP-switch for setting of range, dusk control and delay function (microwave sensor)
- Life time: L70 50,000h Ta25°C



LITELINE BASIC IP44



GTIN	Type	Colour temperature	Luminaire lumen	Luminaire efficiency	Effect luminaire
7392971148946	600, On/Off	3000K	2000lm	111lm/W	18W
7392971148953	600, On/Off	4000K	2100lm	117lm/W	18W
7392971148960 ¹⁾	600, Microwave sensor	3000K	2000lm	111lm/W	18W
7392971148977 ¹⁾	600, Microwave sensor	4000K	2100lm	117lm/W	18W
7392971140247 ²⁾	1200, On/Off	3000K	3530-4480lm	<118lm/W	28-38W
7392971140254 ²⁾	1200, On/Off	4000K	3670-4630lm	<122lm/W	28-38W
7392971140261 ²⁾	1200, Microwave sensor	3000K	3530-4480lm	<118lm/W	28-38W
7392971140278 ²⁾	1200, Microwave sensor	4000K	3670-4630lm	<122lm/W	28-38W

