


Cable Gland Brass IP68 Metric

- Integrated anchorage
- Protection against twisting
- Easy-to-install



* IP69K tested for M12-M25, M50 & M63

Material	Brass nickel plated (CuZn39Pb3)	Colour	Brass nickel plated
Lamellar insert	Polyamide PA6 V-2	Test standard	EN 62444 / UL514B
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR	VDE licence	40020901
O-ring	Nitrile Rubber NBR	UL / CSA-File	E140310
Ingress protection	IP68 - 5 bar, IP69K*	SEV licence	02.1465
Temperature range	-20°C....+100°C (dynamisk) -40°C (static, short term)	Halogen-Free	Ja

E-number	Connection thread	For cable Ø mm	L mm	H mm	SW1 mm	E1 mm	Pcs/pack
1476001	M12x1,5	3 - 6	5.00	25	14.00	15.50	100
1476002	M16x1,5	5 - 9	5.00	30	17.00	19.00	100
1476003	M20x1,5	9 - 13	6.00	33,5	22.00	24.00	100
1476004	M25x1,5	11 - 16	7.00	36,5	27.00	30.00	50
1476005	M32x1,5	14 - 20	8.00	38	34.00	36.00	25
1476006	M40x1,5	19 - 27	8.00	41	43.00	46.00	10
1476007	M50x1,5	24 - 35	9.00	49,5	55.00	60.00	5
1476008	M63x1,5	32 - 42	10.00	52,5	65.00	70.00	5

Created: 24/01/2024 08:49:55. Created from: https://www.rutab.com/our_products/cable-glands/cable-glands-brass/metric-thread/cable-gland-brass-ip68-metric-product?pdf=true&=rnd638416829955325319