


Cable Gland Brass IP68 long thread Metric

- Long connection thread
- Integrated anchorage
- Protection against twisting
- Easy-to-install



*IP69K tested for M12-M25, M50 & M63

Material	Brass nickel plated (CuZn39Pb3)	Colour	Brass nickel plated
Lamellar insert	Polyamide PA6 V-2	Test standard	EN 62444 / UL514B
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR	VDE licence	40020901
O-ring	Nitrile Rubber NBR	UL / CSA-File	E140310
Ingress protection	IP68 - 5 bar, IP69K*	SEV licence	02.1465
Temperature range	-20°C....+100°C (dynamisk) -40°C (static, short term)	Halogen-Free	Ja

E-number	Connection thread	For cable Ø mm	L mm	H mm	SW1 mm	E1 mm	Pcs/pack
1476011	M12x1,5	3 - 6	10.00	30	14.00	15.50	100
1476012	M16x1,5	5 - 9	10.00	35	17.00	19.00	100
1476013	M20x1,5	9 - 13	10.00	37,5	22.00	24.00	100
1476014	M25x1,5	11 - 16	11.00	40,5	27.00	30.00	50
1476015	M32x1,5	14 - 20	13.00	43	34.00	36.00	25
1476016	M40x1,5	19 - 27	13.00	46	43.00	46.00	10
1476017	M50x1,5	24 - 35	14.00	54,5	55.00	60.00	5
1476018	M63x1,5	32 - 42	14.00	56,5	65.00	70.00	5