



Adapter Polyamid RAL 7035 PG - Metrisk

Spesifikasjon

MATERIALE	Polyamid 6 glasfiberforsterket
TEMPERATUROMRÅDE	-40°C....+100°C
FARGE	Lysgrå RAL 7035
HALOGENFRI	Ja

Varianter

EL-NUMMER	YTTERGJENGE	INNERGJENGE	L MM	H MM	L3 MM	SW MM	E MM	ANTALL/PKN
1241757	PG7/12,5	M12x1,5	9	27	15,5	16	18	25
1241758	PG7/12,5	M16x1,5	9	27	15,5	20	22	25
1241760	PG9/15,2	M16x1,5	9	27	15,5	20	22	25
1241761	PG9/15,2	M20x1,5	9	27	15,5	24	27	25
1241763	PG11/18,6	M20x1,5	9	27	15,5	24	27	25
1241765	PG13,5/20,4	M20x1,5	10	28	15,5	24	27	25
1241767	PG16/22,5	M20x1,5	10	28	15,5	27	29	25
1241768	PG16/22,5	M25x1,5	10	28	15,5	29	32	25
1241769	PG21/28,3	M25x1,5	12	30	15,5	33	36	10
1241770	PG21/28,3	M32x1,5	12	30	15,5	36	40	10
1241771	PG29/37,0	M32x1,5	12	19	15,5	42	45	10
APM 29/50	PG29/37,0	M50x1,5	12	30	15,5	55	61	10
APM 36/40	PG36/47,0	M40x1,5	14	21	15,5	53	59	10
APM 36/50	PG36/47,0	M50x1,5	14	32	15,5	55	61	10
APM 36/63	PG36/47,0	M63x1,5	14	32	15,5	68	75	10