


Cable Gland Brass IP68 PG

- Integrated anchorage
- Protection against twisting
- Easy-to-install



Material	Brass nickel plated (CuZn39Pb3)	Ingress protection	IP68 - 5 bar
Lamellar insert	Polyamide PA6 V-2	Temperature range	-20°C....+100°C (dynamisk) -40°C (static, short term)
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR	Colour	Brass nickel plated
O-ring	Nitrile Rubber NBR	Halogen-Free	Ja

E-number	Connection thread	For cable Ø mm	L mm	H mm	SW1 mm	E1 mm	Pcs/pack
1460402	PG7/12,5	3 - 6,5	5.00	24	14.00	15.50	100
1460405	PG9/15,2	4 - 8	6.00	29	17.00	19.00	100
1460408	PG11/18,6	5 - 10	6.00	29,5	20.00	22.00	50
1460410	PG13,5/20,4	6 - 12	6.50	31,5	22.00	24.00	50
1460412	PG16/22,5	10 - 14	6.50	31,5	24.00	26.70	50
1460414	PG21/28,3	13 - 18	7.00	34	30.00	33.50	50
1460417	PG29/37,0	18 - 25	8.00	39	40.00	44.00	25
1460419	PG36/47,0	24 - 32	9.00	45	50.00	54.00	10
1460421	PG42/54,0	30 - 38	10.00	49	57.00	61.00	5
1460423	PG48/59,3	34 - 44	10.00	52	64.00	69.00	5